



Proventeq Migration Accelerator

User Guide

Version: 8.11

01 July 2024

Authored by: Proventeq

Status: Published

PROVENTEQ MIGRATION ACCELERATOR	0
1. GETTING STARTED.....	6
1.1. PROJECT PLANNING	7
1.2. MIGRATION TERMS AND CONCEPTS	7
1.3. SUMMARY OF MIGRATION PROCESS	11
1.4. VERIFY THE MIGRATION.....	12
1.5. COMMUNICATE WITH END-USERS	12
1.6. HIGH-LEVEL MIGRATION PLAN	12
2. PRODUCT LICENSE ACTIVATION.....	15
2.1. ONLINE ACTIVATION	15
2.2. OFFLINE ACTIVATION	15
2.3. LOG INTO PROVENTEQ SUPPORT SYSTEM (ZENDESK)	16
3. UI OVERVIEW	17
3.1. NAVIGATION PANEL.....	17
3.1.1. MANAGING CONNECTIONS.....	17
3.1.2. MIGRATION JOB MANAGEMENT	18
3.1.3. LICENSING	19
4. MIGRATION JOB CREATION	20
4.1. ADD A NEW SOURCE CONNECTION	20
4.1.1. ADDING A FILE SHARE AS A SOURCE	21
4.1.2. ADDING SHAREFILE AS A SOURCE.....	22
4.1.3. ADDING DOCUMENTUM SOURCE.....	24
4.1.4. ADDING BOX SOURCE.....	29
4.1.5. ADDING IMANAGE SOURCE	30
4.1.6. ADDING FILENET P8 SOURCE.....	31
4.1.7. ADDING ALFRESCO SOURCE	35
4.1.8. ADDING OPENTEXT CS SOURCE	36
4.1.9. ADDING OPENTEXT EDOCS SOURCE	38
4.1.10. ADDING M-FILES SOURCE	40
4.1.11. ADDING ORACLE UCM SOURCE	40

4.2. ADD A NEW TARGET CONNECTION	43
4.2.1. ADDING SHAREPOINT ONLINE TARGET	44
4.2.2. CONFIGURATION WHEN CONNECTING TO TENANT	51
4.2.3. ADDING M-FILES TARGET	52
4.2.4. ADDING AZURE STORAGE	53
4.2.5. ADDING SHAREPOINT 2019	55
4.2.6. ADDITIONAL JOB SETTINGS	55
5. MIGRATION JOB DASHBOARD.....	58
5.1. DISCOVERY STATUS.....	58
5.2. LOAD STATISTICS	59
5.3. MIGRATION PHASES	59
5.4. EXPLORER	59
5.5. REPORTING	60
5.5.1. DISCOVERY REPORT.....	60
5.5.2. PRE-CHECK REPORT	61
5.5.3. MIGRATED ITEMS REPORT	61
5.5.4. FAILED ITEMS REPORT	62
5.5.5. ERROR SUMMARY REPORT	62
5.5.6. MIGRATION AUDIT REPORT	62
5.5.7. PERFORMANCE REPORT	62
5.6. ACTIVITY LOG	63
6. PHASE 1 – DISCOVERY AND ANALYSIS.....	64
6.1. STARTING DISCOVERY.....	64
6.1.1. BACKGROUND OPERATIONS.....	65
6.1.2. DISCOVER ERRORS	66
6.1.3. FILTER DISCOVERY OPTIONS.....	66
6.1.4. VERSION FILTERING	67
6.1.5. DISCOVERY FILTERS	67
6.1.6. RESET DISCOVERY	68
6.2. DELTA MIGRATIONS.....	68
6.3. ITEMS LIST	70

6.3.1. ITEM LEVEL INFORMATION	71
6.3.2. ITEMS DETAILS	72
6.3.3. SOURCE VIRTUAL COLLECTIONS	74
6.3.4. TARGET STRUCTURE ENTRIES	74
6.3.5. PROCESSING HISTORY	74
6.4. PRE-CHECKS	74
6.4.1. CHANGING PRE-CHECK SETTINGS.....	75
6.4.2. RUNNING PRE-CHECKS	81
6.4.3. REVIEW AND CORRECTING PRE-CHECK ISSUES	81
7. CREATING DETAILED MIGRATION PLANS.....	84
7.1. INTRODUCTION	84
7.1.1. CONTENT TYPE PLANNING	84
7.1.2. STRUCTURE MAPPING	85
7.1.3. SECURITY	85
7.1.4. SHORTCUT LINKS/EMBEDDED LINKS PROCESSING	85
7.2. RECREATE USING SOURCE HIERARCHY	87
7.3. RESTRUCTURE USING FOLDERS/CONTAINERS	87
7.3.1. SHAREPOINT STRUCTURE BASICS	88
7.3.2. COMPLETING STRUCTURE MAPPING OVERVIEW	89
7.3.3. STRUCTURE MAPPING EXAMPLES.....	90
7.4. RESTRUCTURE USING ITEM METADATA	93
7.4.1. CONFIGURATION STEPS FOR RESTRUCTURING USING ITEM METADATA	94
7.4.2. ADVANCED TARGET ASSIGNMENT EXPRESSIONS.....	95
7.4.3. DEFAULT TARGET ASSIGNMENT	96
7.4.4. METADATA STRUCTURE MAPPING CONFIGURATION STEPS	97
8. PHASE2 – CONTENT TYPES	99
8.1. MAPPING CONTENT TYPES.....	99
8.1.1. REVIEWING DEFAULT CONTENT TYPE MAPPINGS	99
8.2. TARGET METADATA MAPPING.....	100
8.2.1. POPULATING TARGET USING SOURCE METADATA.....	101
8.2.2. POPULATING TARGET USING CONSTANT VALUE.....	102


8.2.3. POPULATING TARGET USING FUNCTIONS	102
8.2.4. POPULATING TARGET USING POWERSHELL	106
8.2.5. USING DOCUMENT ID SERVICE.....	111
8.3. CUSTOM CLASSIFICATION	111
8.3.1. CREATING A CUSTOM CLASSIFICATION	112
8.3.2. CUSTOM CLASSIFICATION SCRIPTING OBJECTS	114
9. SECURITY MAPPING.....	117
9.1. SECURITY ENTITIES: USER, GROUP, PERMISSIONS	117
9.2. CONFIGURING USER SECURITY MAPPING	118
9.2.1. PROCESSING EMPTY SOURCE USER FIELDS.....	120
9.2.2. VERIFYING USER MAPPINGS	120
9.2.3. SAMPLE SECURITY MAPPINGS	120
10. PHASE 2 – GENERAL SETTINGS.....	122
11. PHASE 3 – MIGRATION PHASE.....	125
11.1. MIGRATION STEPS.....	125
11.2. PROBLEM ITEM PROCESSING	127
11.2.1. EMPTY FILES	127
11.3. TRANSFORM WARNING	128
11.4. STEP 1 EXTRACT – EXTRACT METADATA	128
11.5. STEP 2 CLASSIFY - ASSIGN TARGET CONTENT TYPE.....	129
11.6. STEP 3 TRANSFORM - CREATE ITEM MANIFEST	130
11.7. STEP 4 LOAD – MIGRATE TO TARGET	130
11.8. MIGRATION CONSIDERATIONS	131
11.9. UNDO MIGRATION	131
11.10. RESOLVING MIGRATION ERRORS	132
11.11. SHORTCUT LINKS MIGRATION	132
11.12. VERIFY AND COMMUNICATE WITH END USERS	133
12. POWER BI REPORTS.....	134
12.1. GENERAL DISTRIBUTION OF CONTENT.....	134
12.2. PRE-MIGRATION CHECKS- VERSION CONTINUITY.....	135
12.3. PRE-MIGRATION CHECKS- PATHS AND NAMES.....	136

12.4. PRE-MIGRATION CHECK – FOLDERS & FILES.....	137
12.5. GENERAL USAGE OF CONTENT	138
12.6. CONTAINER ANALYSIS	138
13. APPENDIX	140
13.1. LICENSING.....	140
13.2. DISCOVERY FILTERS.....	140
13.2.1. DISCOVERY FILTER FOR SHAREFILE.....	140
13.2.2. DISCOVERY FILTER FOR FILESHARE.....	141
13.2.3. DISCOVERY FILTER FOR DOCUMENTUM	143
13.2.4. DISCOVERY FILTER FOR OPENTEXT.....	147
DISCOVERY FILTER FOR FILENET P8	148
13.2.5. DISCOVERY FILTER FOR IMANAGE.....	150
13.2.6. DISCOVERY FILTER FOR M-FILES	151
13.2.7. DISCOVERY FILTER FOR ALFRESCO	152
13.2.8. DISCOVERY FILTER FOR ORACLE UCM	152
13.2.9. DISCOVERY FILTER FOR HUMMINGBIRD/EDOCS.....	152
13.2.10. DISCOVERY FILTER FOR BOX.....	153
14. APPENDIX 2 - PROGRAMMING	155
14.1. BUILT-IN FUNCTIONS	155
14.1.1. STRING FUNCTIONS	155
14.1.2. MATH FUNCTIONS	156
14.1.3. DATE FUNCTIONS.....	156
14.1.4. MISC FUNCTIONS.....	156
14.1.5. OCR FUNCTIONS	157
14.2. CREATING LOOKUP TABLES FOR CUSTOM FUNCTIONS	157
14.2.1. USING THE IMPORTED DATA	159
14.2.2. BOX API CONSUMPTION	160

1. GETTING STARTED

Proventeq Migration Accelerator (PMA) is a versatile enterprise grade migration engine that is deployed as a Windows application. It allows you to configure the different source and target system connections in the migration engine, perform content analysis, set up advanced content transformation rules and execute and monitor the migration. This release supports migrations from Citrix ShareFile, Windows File System, Documentum(SQL and Oracle), i-Manage, BOX, FileNet P8, Alfresco, OpenText CS (SQL and Oracle), OpenText E-Docs(SQL),M-Files, Oracle UCM(SQL, Oracle,DB2). Valid targets are SharePoint Online, File System and M-Files. Note: Not all sources support migrations to File System or M-Files. Contact Technical Support for details.

PMA has been designed with flexibility in mind, so it can be configured and/or extended to address any kind of content migration requirement. Migration Accelerator provides an interactive user interface to configure, migrate, verify, and enhance the quality of migrated content.



Before a migration begins it is critical to understand the data within the existing environment and how it should be represented in the target. This is part of the migration planning process and PMA provides features that allow you to view and then define how this data is migrated and should be presented in the target.

NOTE: Throughout this document the term **Migration** is used. In-fact, Migration of data is always carried out by copying of the data. The process of migrating data to the target does not modify or delete the source data.

NOTE: Information on software and hardware prerequisites and product installation are contained in the Proventeq Content Productivity Suite Installation Guide. This guide presumes the software installation is complete.

1.1. Project Planning

Proventeq Migration Accelerator is a sophisticated migration product, so it is important to plan the migration to ensure that the migration runs smoothly.

Questions to ask when planning for migration include:

- What systems to migrate, their physical location and how much of the data is to be migrated.
- What requirements/expectations are there regarding project milestones, migration completion.
- How to split the migration to make it manageable.
- Differences between the Source and Target in terms of metadata, users, security, and folder structure.
- Should the existing folder structure remain or be changed.
- Do existing access permissions need to be carried over to the target.
- How will end-users be affected, communication plans for end user.
- Source system readiness – Ensuring any documents are ‘check-in’ prior to discovery, that source system is in a good state of health.
- Target system readiness.
- What to do with the Source once migration has been completed.

When starting a migration project, the end-users are a vital part of a successful project. Communication is important and end-users need to know.

- Why the content is being migrated
- What the benefits will be to them
- When the migration is going to happen
- What the expectations are upon them

Any upfront communication also allows users to do any clean up prior to the migration and as a result less data will need to be migrated. End-users will also need to know what the new environment will be, how it will be structured and how to access their data after the migration. Some training may be required for them to take full advantage of the new environment.

NOTE: It's important to understand that by default the location data being migrated to is new and so users should not be working in that area, potentially manipulating folders or documents in locations that are actively being migrated to. If it's essential for this to be allowed, contact technical support to understand the ramifications and potential workarounds.

1.2. Migration Terms and Concepts

This section describes important terms and concepts that are used throughout this guide. It's strongly recommended that you read and understand this section before reviewing the rest of the User Guide.

Source

The Source is where items are to be migrated from.

Target

The Target is where items are going to be migrated to.

Migration Jobs

Migration jobs are the basic framework for a migration.

A Migration Job consists of: -

- Details of Source and Target
- Settings to determine how source data should be transferred in the target
- Settings to control the Migration.

All operations run within the context of a Migration job. Migration projects are generally split into multiple migration jobs. The order in which the migration jobs get processed depends upon criteria such as data volume and business priorities etc.

Staging Database

This is the SQL database that gets created during the product installation. It holds all the configuration information that will be specified as well as the metadata of every source item and their migration status.

Discovery

Discovery runs in the context of a migration job and is the first operation that needs to be run after a migration job is created. During Discovery, information on items, folder/container structures, types of content and security information is collected from the source specified in the current Migration Job and stored in the PMA staging database. Item contents are **not** captured during discovery.

The items discovered can be seen using the **Items List** feature.

Depending upon the size of the environment, Discovery could take several hours or more to complete.

Containers

This term is used to describe an object which can contain items. So a Folder, a Document Library, cabinet, workspace are all different types of Containers.

Pre-Checks

The Pre-Checks feature is set of configurable, pre-defined checks that are run against the information gathered by the Discovery process. It can identify many potential issues that may prevent a successful migration into the target, looking at things like target system restrictions, limitations, empty files and duplicate file names. The result of running Pre-check is a PowerBI report where issues can be reviewed.

Example of a Power BI report after running **Pre-Checks**.




FIGURE 0 - SAMPLE POWER BI REPORT

You can also view the above data using the Pre-Check report.

Migration Settings

These settings control several features related to how data is migrated.

The **Structure Mapping** feature gives control over how the folders/containers in the source should be represented in the target. It provides the ability to simply use the existing hierarchy structure or restructure the folders as part of the migration.

Content Types Terms

Metadata is the term for properties of an item, for example Author or Created Date.

Content Type – A content management system will contain many types of items such as document, folders, invoices etc. These are known as ‘Content Types’. In some systems these may also be known as Document Types/Classes/Categories or Object Types. There are both Source Content Types (what the source system supports) and Target Content

Types (what the target system supports). Each content type may have different metadata fields associated with it.

The **Content Type Mapping** feature controls how properties of a particular Source Content Type are mapped to a specified Target Content Type. For example, when an item of Source Content Type 'Invoice' is migrated, an item of type 'Legacy Invoice' (as defined by Content Type Mapping settings) should be created in the target and the metadata mapping information (see below) will be used to determine how metadata properties in the target item should be populated. PMA ships with very useful default mappings and these can be customised as required.

The **Metadata Mapping** feature controls how each target metadata property is populated for each target content type e.g. how the 'Description' or 'Amount' metadata properties is populated for the 'Legacy Invoice' Target Content Type.

PMA ships with very useful content type mapping defaults and applies these (this is termed **Automated Content Type Mapping**). They can be customised as required.

Custom Classification is an advanced feature that allows items in source to be mapped and processed based upon their metadata properties, overriding the content type assigned in source. See [Custom Classification](#) for more information.

Security Mapping is used to define how Users, Groups and permissions types from the source should be represented on the item in the target. For example if the Created By of a source document is "Percy Shelley" then in the target the Created By should be Percy.Shelley@acme.com (because in SharePoint this field is required to be an smtp address).

Shortcuts Links

These are items in the source system which are pointers to an item in another location. Some platforms support these calling them Shortcuts or Links. In some occasions there may even be several of these links pointing to a single source document, this is known as multi-filing.

Note: The use of shortcuts in SharePoint is generally not recommended.

Embedded Links

These are pointers contained within documents that link to another item. e.g. a Word document stored in Documentum may contain an Embedded Link to another Documentum item.

Note: Both the shortcut links and embedded links features will impact migration speed if enabled.

Migration

Migration is a set of individual steps listed below to prepare and then load items into the target. These sequential steps can be executed individually so that in the early phase of the migration project the output of each can be verified before executing subsequent steps.

The **Item Manifest** is a data structure that contains all the information about an item to be migrated, excluding the item content itself. It will contain the location where an item should be migrated to, all the values for the target metadata fields and so on. Steps 1-2 provide the information for Step 3 which creates this structure for each item.

The processing steps are sequential, so an item will first be processed by Step 1, then Step 2 and so on.

Step 1 Extract – Captures metadata for each source item into the PMA Staging database.

Step 2 Classify – Determine what the target content type of the item should be based upon the extracted meta data from step 1, or custom classification rules and source->target content type mapping configuration.

Step 3 Transform – Uses the output from Step 2 as well as information from structure, content type and security settings to create a data structure for each item called the Item Manifest.

Step 4 Load – Retrieves the item content from the source and combines it with the Item Manifest from Step 3 and uploads this into the target.

Packaging

To improve migration speed, items are ‘packaged’ before uploading to SharePoint.

Note: During the pilot phase of the migration, or after reconfiguration, it is strongly recommended to run each of the 4 steps above separately and the results reviewed before executing the next step.

1.3. Summary of Migration Process

A migration is a project where several **Migration Jobs** are created, each specifying details of a **Source Connection** and a **Target Connection**.

In the **Discovery Phase**, the **Discovery process** is run for each job to build an inventory of items in the source and gather basic details of each. The details gathered are visible using the **Items List** feature and can be analyzed using the **Pre-Checks** feature to identify potential issues (as shown in the **Power BI** reports). The **Power BI** reports also displays lots of other useful information to help the customer understand the content to be migrated.

In the **Migration Preparation Phase**, the user can review existing **Folder Structures**, **Content Types** and **Security Information**. Using an understanding of business requirements and the environment, **Structure Mapping** can be used to define what the target folder hierarchy should look like. **Content Mapping** can be used to control how the **metadata** fields in source items should be moved to the target and finally, **Security Mapping** used to specify how user and security information in the source should be transferred to the Target.

Once these are complete, the **Migration Phase** can begin. Items are processed based upon these settings above to create an **Item Manifest** for each item which in the **Load** step is

combined with the retrieved item content and uploaded to the **Target**. During the **Load** step, if the option **Update Embedded Links** is select then these will be updated in Items as they are migrated.

If there is a requirement to migrate shortcuts then the **Shortcut Links Migration** features can be used to migrate these after all items have been successfully migrated.

1.4. Verify the Migration

Like any data migration, it's critical to ensure that data has been migrated as expected. Special attention needs to be paid during the pilot phase, reviewing the processing of different content types, all of the source meta data are migrated as required, items are migrated to the correct location etc.

As with any migration, a comprehensive User Acceptance Testing (UAT) plan must be in place to ensure the business users are satisfied there are no issues and the migration is meeting the business requirements.

1.5. Communicate with End-Users

End- users need to be aware that their data is being migrated and once the data has been migrated they need to check that they can access the data. It is worth considering providing training for End-Users so that they can learn the new features of their environment. Take into account that End-Users may be away for an extended period of time, for example maternity leave or long term ill health. Eventually you will need to decide what to do with the original Source environment.

1.6. High-Level Migration Plan

- **Configuration**
 - Apply for a PMA License(s).
 - Create Migration Job(s)
 - Specify details of source.
 - Specify details of target.

Both will require permission to access the source/target.

- **Phase 1 - Discovery**
 - ❖ Run discovery
 - ❖ Run pre-checks, review output and take corrective action were necessary.
 - ❖ Understand existing source folder structures, content types and security.
 - ❖ Using understanding of source, have detailed discussions with the customer regarding metadata. What metadata is on each content type, if and how that should be represented in the target.

- ❖ Discuss with customer, requirements for target folder hierarchy structure.
- ❖ Understand data volumes in various locations to help develop plan for order of data migration.
- ❖ Using understanding of existing data and business migration requirements go to phase 2 to apply these.
- ❖ Work with the business to develop UAT program.

Based upon the outcome of discovery, you may then use this to decide overall migration architecture i.e. The numbers of application servers etc. that are required.

- **Phase 2 - Migration Preparation**

- Structure Mapping - Choose appropriate Structure mappings option and create structure mapping entries if necessary. Some configuration of the target system may also be required.
- Content Type Mapping- Understanding existing content in detail and how it should be reflected in the target.
- Metadata – For each content type, what metadata properties are used currently; what and how should these fields be moved into the target.
- Security Mapping - Setup user, group, and permission mapping to assign new values to existing user and groups etc. associated with the existing data in the source.
- Review migration options, in particular Embedded Link resolution.

To ensure the migration runs smoothly and will meet business needs, it's **strongly recommended** to review and get 'sign off' on these data migration settings with the appropriate parties.

- **Phase 3 - Migration**

Note: Executing a step will also execute the previous steps if not already run.

- Execute **Step 1- Extract**, review extracted meta data from source system and ensure it is correct.
- Execute **Step 2 – Classify**, review content types that have been assigned to items.
- Execute **Step 3 – Transform**, this will use the information in structure mapping, content types etc. and create a package of data for each item (terms an item manifest) which should be reviewed and will then be used by step 4.
- Execute **Step 4 – Load**, will use the item manifests created by step 3, retrieve the actual item from the content source and load it into the target.
- Migrating Shortcuts Links- After migration, execute the Shortcut Links Migration which will migrate any shortcuts in the source system into the target. Note: It's not recommended to continue to use shortcuts in SharePoint.

- **Verification** - After migration, review the migrated data to ensure
 - Migrated to correct location

- For each source Content type, meta data and item content are correct
- Security information is correct
- Links between items are working (if option to convert was selected)
- Shortcuts are recreated and working (if option to migrate was selected)

2. PRODUCT LICENSE ACTIVATION

Start the product from the desktop icon or by selecting Start and navigating to Proventeq Content Suite. When the product starts without a license, all features will be disabled, and it will display the license activation screen.

To activate a licence online the server must be able to successfully connect to <https://api.proventeq.com>. If the connection is successful the browser will display “Hello”, if this fails you may need to change server/firewall configure or use Offline Activation.

2.1. Online Activation

The License key will have been provided to you along with the software download link. Enter the Licence key and click **Activate Online**. This will authenticate the License key and register the product.




FIGURE 1 - ONLINE LICENSE ACTIVATION

2.2. Offline Activation

If it's not possible to activate the licence via the internet it is possible to Activate Offline. Enter the License key provided and select **Offline Activation**. Click **Generate Activation Request file**. It will generate a file .REQ file that should be sent to license@proventeq.com . On receiving the Activation response file(.RESP) from Proventeq, click **Upload Activation Response** to activate the product.

License Activation

Enter your product license key and select Online or Offline Activation.

License key *

Online Activation Offline Activation

Use Offline Activation if server cannot use Online Activation

Enter your license key and select the "Generate Activation Request File". Email the generated .req file to license@proventeq.com.

Once processed by Proventeq, you'll receive an activation response file (.resp). Copy .resp file to the PMA server and select the "Upload Activation Response". Select the .resp file to upload and activate the license.

Generate Activation Request File Upload Activation Response

FIGURE 2 - OFFLINE LICENSE ACTIVATION

Once licence is activated, select the Home button to goto the PCS Content Suite Home page.

2.3. Log into Proventeq Support system (Zendesk)

Proventeq uses the popular support system Zendesk for storing knowledge base, documentation as well as ticket tracking. The PCS client contains helpful Learn more... links which link to relevant KB articles and also errors messages that may occur in migration may also refer to KB articles. To view these articles, you are required to be logged into Zendesk.

We strongly recommend that you log into your Zendesk account from the PCS system in order to make the most of these features. If you do not have an account, please email pcs.support@proventeq.com. If you are delivering the project on behalf of a customer, include the customer's name in the request.

NOTE: When creating a support ticket, we strongly recommend that you attach screenshots, PMA log files along with the steps to reproduce the issue as this will help us to resolve issues more quickly.

3. UI OVERVIEW




FIGURE 3 - HOME SCREEN

Throughout the product there are [Learn more](#) links which can assist you by opening the relevant section of this online User Guide.

Note: The PMC desktop client is a single user only client. This means that only one user can operate the client on a particular server, irrespective of what user account they may be logged into on that system.



3.1. Navigation Panel


On the left-hand side is the navigation panel. These options are used to carry out tasks that are not related to a specific job. It consists of: -



- Navigate to Home screen
- Managing Connections
- Managing Insight jobs (if licensed)
- Managing Migration jobs (if licensed)
- Help - Access to guides and support portal.
- Access to License and product information

3.1.1. Managing Connections

A connection is a location that can be migrated from, which is called a 'Source Connection' or a location to be migrated to which is called a 'Target Connection'. They will contain settings related to the relevant system and these connections can be reused across migration jobs.

These connections can either be added to PMA during the migration job creation wizard (as shown earlier) or separately in Manage Connections.

To create a connection using the Manage Connections option, click on the  icon in the navigation panel from where you can create or edit Source and Target connections.

Click on  to add a new connection or  to edit existing connection.





FIGURE 4 - ADD/EDIT CONNECTIONS

3.1.2. Migration Job Management

To manage jobs, click on  in the Navigation Panel. New jobs can be created and the properties of existing jobs can be viewed.





FIGURE 5 - MIGRATION JOB MANAGEMENT

Exporting Job Settings

Some of the settings on a job can be used by other jobs by selecting the job Export option . This will export settings associated with structure mapping, content type mapping and security mappings to a file which can be imported when creating a new job. This makes it simple to share settings across PMA servers.

NOTE: Export settings does not save custom content type information.

3.1.3. Licensing

License activation (online or off-line) as well as license information and consumption can be found here.

Version: 8.6.282.1305

License state: Activated

MikeB-James test

License Key

License Type: Trial

Discovery Items Limit: 100,000

Discovered Items: 0

Processing Items Limit: 20,000

Processed Items: 18,963

Processing Size Limit (MB): -1

Processed Size (MB): 5,122.879

Instances Limit: 1

Container Item Limit: Unlimited

Activation Date: 17 February 2023

Last Update Date: 16 March 2023

Expiry Date: 19 March 2023

License Validity in Days: 30

Licensed Sources: File System, SharePoint 2019, SharePoint Online, Oracle UCM, Oracle UCM (10G), FileNet, FileNetAPI, Alfresco, Offline, WorkSite, OpenText eDocs, Meridio, Drupal8, KCenter, AmazonS3, FileNetPanagon, Documentum, Documentum, OracleCloud, Box, Liferay, MFiles, AzureStorage, ShareFile, GSuite, OpenTextCS, OpenTextAS

For technical assistance access our knowledge base and support system at <https://support.proventeq.com>

Copyright © 2023 Proventeq Ltd. All Rights Reserved.

FIGURE 6 - LICENCE INFORMATION

For more information on Discovery Status, Migration Status and Migration phases see [Discovery Status](#)


4. MIGRATION JOB CREATION

A migration project is typically broken down into one or more Migration Jobs. For each job, the source system and source path, together with the target system and target path is specified. By selecting a particular job within the client, all other operations work in the context of those settings. It's possible to switch between migration jobs in the client but only one operation can be executing at any one time on the server.

Often several jobs are created even if there is just one source and one target. In doing so it's possible to break down the overall migration into several manageable chunks by specifying specific source paths for migration or other filter criteria.

Depending upon the project, several PMA servers may be required. It is recommended that the Source and the PMA server(s) should be in the same location (i.e. to keep latency as low as possible).

NOTE: If using several PMA servers together with embedded link resolution or shortcut link migration features, ensure such links are not across PMA systems.

Migration Job creation is simple using the job creating wizard which is available using the  Migration icon on the Navigation Panel. Source and Target Connections can either be created during the wizard or from the Connections option displayed in the Navigation Panel.

4.1. Add a New Source Connection

Items are migrated from the system specified by a source connection. Relevant security credentials will be required.




FIGURE 7 - ADDING SOURCE CONNECTION FROM JOB WIZARD


Select the source platform to migrate from.

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#)



Only platforms that are licensed for migration will be listed above.

NOTE: In most sources below, it's possible to filter the folders that are displayed using the  icon. This only affects the folders that are displayed and is NOT the way to apply a filter to what should be discovered. Use Change Settings on Discovery to apply filters to discovery.

4.1.1. Adding a File Share as a Source

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#)




FIGURE 8 - SELECTING SOURCE SYSTEM TYPE

Provide a name for this Source and specify the location or select the Browse icon.

Note: By default, mapped or Network Drives will not be shown in the Browse window, to resolve this follow steps in this article <https://support.proventeq.com/hc/en-us/articles/4409959298321>

Source Plugin: Select “Default Source Plugin”

Test the Connection before adding the Source Connection

Select the root folder to migrate from




FIGURE 9 - SELECTING FILE SYSTEM ROOT FOLDER TO MIGRATE

4.1.2. Adding ShareFile as a Source

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#)

Source System
ShareFile

Name *
 ShareFile Migration Trial

Base Uri *
 https://sfacme.sharefile.com

Client Id *
 q45JHWRUY985763IRYWUYYWT7EYTKIUTY9RT

Client Secret *

Username *
 admin@acme.com

Password *

Timezone

Test Connection Add

FIGURE 10 - TESTING SHAREFILE SOURCE CONNECTION

The following fields need to be configured for a ShareFile Connection:

Name: Name of connection, to uniquely identify the connection within the workspace.

Base URL: URL of the system ShareFile. E.g. <https://sfacme.sharefile.com>

The Client id and client secret below can be obtained by clicking on Get an API Key on the following site <https://api.sharefile.com>

Client id: Client ID of the Source ShareFile.

Client Secret: Client Secret of the Source ShareFile.

Username: Username for connecting to ShareFile. The user should be an administrator.

Password: Password for the above-mentioned user or application specific password if using MFA.

Note: If system is using Multi Factor Authentication (MFA) then it's necessary to generate an application specific password and use the password it generates here.

Steps:

Log into customer domain e.g. <https://sfacme.sharefile.com>

Go to Personal Settings > Personal Security > Two-Step Verification > scroll down to Application-Specific Passwords and click Generate Password.

Full details here <https://support.citrix.com/article/CTX277723#generate>

Time Zone: If Source and Target are in different time zones.

Specify the exact parent folder to migrate from

SOURCE 




FIGURE 11 - SELECTING SHAREFILE ROOT FOLDER TO MIGRATE

Browse and select **Folder** using the folder selection dialog.

See **Error! Reference source not found.** for more information on migrating from ShareFile e.g. how to create API Key etc. Personal Files, Content types etc.

4.1.3. Adding Documentum Source

Documentum has a database and a file storage component so access details to both may be required. The exact information required depends upon several factors.

- Whether to use Documentum API for Discovery and retrieval of items.
- Whether Documentum is using an Oracle database or a Microsoft SQL database.
- Whether using retrieval method of File Store or API

If the option to use API for Discovery and Migration below is selected then the API is for Discovery and retrieval so then only server URL, username and password are required.


Retrieval Method controls how items should be retrieved from Documentum. The API retrieval method means that PMA will call the Documentum API to retrieve items. The File Store method means that PMA will access the Documentum files on disk directly to retrieve content. API method provides improved compatibility/reliability in some scenarios, but File Store can provide faster retrieval because it will bypass the Documentum system.

Add Source Connection



A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#)

Source System

 Documentum (DB)

Name *

API for Discovery and Migration

DB Type

Content Retrieval Method

Retrieval Method

Api

Server URL *

Username *

Password *

Ignored Cabinets

System, Temp, Resources

Test Connection

Add

Source System

Documentum (DB)

Name *

DB Type

Oracle

Host Database Server *

Port*

1521

SID/Service Name

SID Service Name

SID/Service Name *

Schema *

Username *

Password *

Name: Name of connection, to uniquely identify the connection within the workspace.

If the option to use API for Discovery and Migration is selected, then the API is for Discovery and retrieval so only the following details are required. This can make configuration easier, but API methods can be slower than using PMA to access the underlying system directly.

Server URL: REST URL of the target Documentum Content Server. This is normally the hostname/IP address of the Documentum server followed by “:8080/dctm-rest/services” e.g. <http://192.162.19.29:8080/dctm-rest/services>.

Username: This is the Username for connecting to Documentum. The user should be an Administrator of Documentum.

Password: This is the password for the above user.

Ignored Cabinets - Cabinets not to be processed e.g. System,Temp,Resources

If not using API for Discovery and Retrieval(this is the default recommended option)

Select DB Type : SQL or Oracle (type of database used by Documentum)

If using Oracle

Host Database Server: Name of Oracle database server hosting Documentum database.

Port: Port number for Oracle database system

Whether to use SID or Service Name

SID/Service Name:

Database Schema:

Username & Password- Details of account with access to Documentum database.

If using SQL

Server: Name of SQL database server hosting Documentum database.

Port: Port number for Microsoft SQL server database system

Name of Documentum database: Documentum database name

Option to use Integrated Security. If selected the PMA service account (i.e. the account it runs under) will be used to access SQL. If not selected, then required to specify details username and password of a SQL login account with access.

Content Retrieval Method

This setting controls whether items are retrieved using requests to the Documentum API or by PMA accessing the information directly.

API

Retrieval Method

Api

Server URL *

Username *

Password *

Ignored Cabinets

System, Temp, Resources

Server URL: REST URL of the target Documentum Content Server. This is normally the hostname/IP address of the Documentum server followed by “:8080/dctm-rest/services” e.g. <http://192.162.19.29:8080/dctm-rest/services>

Username: : This is the Username for connecting to Documentum. The user should be an Administrator of Documentum.

Password: Password for the above user

Ignored Cabinets - Cabinets not to be processed e.g. System,Temp,Resources

File Store

Content Retrieval Method

Retrieval Method

File Store

Path Overrides *

Ignored Cabinets

System, Temp, Resources

Path Overrides: If the path in the database cannot be resolved from the PMA server, this feature can be used to 'map' that entry to an accessible location. Can also be used when source data is copied to another location.

The details of path overrides can also be specified in a .CSV file and imported. Below is example of formatting required.

```
fileStore,overrideFilepathValue  
fileloc_1,\\fileserv1.acmecorp.com\Fin\US\storage_1  
fileloc_19,\\fileserv1.acmecorp\Fin\UK\storage_19
```

NOTE: The override information is used during the discovery process to create source path URI for items. If the path override is edited after discovery, it may be necessary to reset and rerun discovery for these changes to be processed.

Ignored Cabinets: Cabinets not to be processed e.g. System,Temp,Resources

NOTE: Virtual documents will be migrated as Document Sets in SharePoint so it is necessary to enable this feature on the SharePoint site collection.

4.1.4. Adding BOX Source

×

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#) ↗

Source System

box Box
 ▼

Name *

BoxUri *

BoxUser *

Load JWT from

Inline text
 File

JWT File *
📁

Test Connection

Add

Name: Name of connection, to uniquely identify the connection within the workspace.

Box URL: URL of the Box system. Usually this will be `https://app.box.com`

Box User: Username of Box enterprise admin account

Load JWT from:

The PMA Box connector supports the JWT (JSON web token) method of authentication. The token can either be located in a .JSON file or select 'Inline text' and enter the token in the specified field.

File: Location of a file containing JWT token

Inline text: String containing JWT token

NOTE: When migrating from BOX, API calls are used to discover and retrieve data. This is likely to have an impact on the API limits associated with your BOX system. Therefore it's essential to discuss your API call limits with your BOX Account Manager. See 14.2.2. for details of how migration consumes BOX API


4.1.5. Adding iManage Source

To discovery and therefore migrate from iManage it's necessary to place a copy of the iManage database onto the same SQL server that the PMA Staging database is hosted on. If a hosted iManage system is being used, then contact iManage to request a copy of your database.

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#) 

Source System

 iManage

Name *

Server *

Use Integrated Security

User Name

Password

Database Name *

Content Retrieval Method

Retrieval Method

File Location

Timezone

Test Connection

Add

Name: Name of connection, to uniquely identify the connection within the workspace.

Server Name: Name of SQL server hosting iManage database.

Use Integrated Security – If selected then the account currently logged into will be used to access the iManage database.

Username and password: If **Use Integrated Security** is unselected then specify the username and password of an SQL Login account with access to the iManage database.

Content Retrieval Method:

There are two methods that can be used to retrieve iManage data, “API” or “File Store”. If the iManage system is hosted or encrypted then you **MUST** use the API method. The File Store method means that PMA will retrieve the underlying iManage files rather than use the iManage API. You may choose to copy the files to the PMA server to reduce network impact and improve performance.

File Store retrieval method:

File Location: Optional. If the iManage files have been copied from the iManage server to another location for migration, specify the location here.

Database Alias (optional) Can be used to identify a specific iManage instance.

API retrieval method:

URL: IManage URL

Username: IManage Username

Password: IManage Password

Database Alias (optional) Can be used to identify a specific iManage instance.

NOTE: Migration of Workflows from iManage is not supported

4.1.6. Adding FileNet P8 Source

PMA can either use the FileNet API for both discovery and retrieval or be configured to access the FileNet database directly. It supports FileNet using Microsoft, Oracle or DB2 databases.

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#) 

Source System
+ Filenet

Name *

Service Url *

Username *

Password *

WorkPlace XT Url *

API for Discovery and Migration

Connection Types

Object Store Name

Host Database Server

The following fields needs to be configured for a FileNet P8 Connection:

Name: Name of connection, to uniquely identify the connection within the workspace.

Service URL: URL of the FileNet Web API service hosted on Content Engine server.

Username: Filenet Username for connecting to FileNet Content Engine. The user should have Administrator privileges. Domain accounts are not supported.

Password: Password for the above user.

WorkPlace XT URL: Normally of the form, e.g. "<http://acmecorpfilenet:9080/WorkplaceXT>".

The FileNet WorkplaceXT is normally hosted on FileNet XT Server.

API for Discovery and Migration: With this toggle off(default), PMA will access the Filenet database directly during discovery and use the FileNet API for retrieval. If toggle selected, the Filenet API will be used for both discovery and retrieval.

Connection Types: Specify the database product used by Filenet. It can either be SQL, Oracle or DB2.

Filenet p8 using Oracle Database

Object Store Name *
Connection Types Oracle
Host Database Server *
Port
<input type="radio"/> SID <input type="radio"/> Service Name
Database Username *
Database Password *
SID/Service Name *
SQL Schema

Host Database Server: Name of Oracle database server hosting Filenet database.

Port: Port number for Oracle database system

Whether to use SID or Service Name

Username and Password: Credentials of account with access to Oracle database

SID/Service Name: Name of SID/Service

SQL Schema: Oracle SQL schema

Filenet p8 using SQL Database

Connection Types
SQL

Object Store Name

Host Database Server

Use Integrated Security

Database Username

Database Password

Database

SQL Schema

Object Store name – Filenet Object store

Host Database Server: Name of SQL database server hosting Filenet database.

Option to use Integrated Security. If selected the PMA service account (i.e. the account it runs under) will be used to access SQL. If not selected, then required to specify details username and password of a SQL login account with access.

Database: Name of Filenet SQL database.

SQL Schema: e.g. dbo

Filenet p8 using DB2 Database

Object Store Name *	DemoStore
Connection Types	DB2
Host Database Server *	
Database	
Port	
Database Username *	
Database Password *	

Object Store name – Filenet object store

Host Database Server: Name of DB2 database server hosting Filenet database.

Database: Name of Filenet SQL database.

Port: Port used to connect to DB2 database.

Username and password: Credentials to access DB2 database.

4.1.7. Adding Alfresco Source

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#)

Source System

Alfresco

Name *

SiteURL *

User Name *

Password *

Use Kerberos

Test Connection Add

Name: Name of connection, to uniquely identify the connection within the workspace.

SiteURL: URL for Alfresco API. This is either in the format

<http://<Alfresco server>:<port>/alfresco/api/-default-/public/cmisis/versions/1.1/browser>

e.g. <http://prodcms:8080/alfresco/api/-default-/public/cmisis/versions/1.1/browser>

or

<http://<Alfresco server>:<port>/alfresco/api/-default-/public/cmisis/versions/1.0/atom>

Username and Password: Details of account with access to Alfresco server

Use Kerberos: Select to use Kerberos

4.1.8. Adding OpenText CS Source

Source System

OpenTextCS

Name *

Server URL *

UserName *

Password *

Source Database

SQL Server

Database Server Name *

Database Name *

Use Integrated Security

User Name

Password

Sql Schema *

Timezone

Test Connection

Add

NOTE: Only OpenText CS using Microsoft SQL is supported at this time. Contact Technical Support for more information.

Name: Name of connection, to uniquely identify the connection within the workspace.

Server URL: URL of OpenText system. <http://<opentextserver>/otcs/cs.exe/>

Username and Password: Details of account with access to OpenText CS server

Source Database: Select whether OpenText is using SQL Server or Oracle as it's backend database.

If using SQL Server

Database server name: Name of Microsoft SQL server storing OpenText database.

Database name: Name of OpenText SQL database

Use Integrated Security – If selected then the account currently logged into will be used to access the database.

Username and password: If **Use Integrated Security** is unselected then specify the username and password of an SQL Login account with access to the database.

SQL Schema: SQL schema name of OpenText Database.

4.1.9. Adding OpenText Edocs Source


To discover and therefore migrate from EDocs, it's necessary to place a copy of the EDocs database onto the same SQL server that the PMA Staging database is hosted on.

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#) 

Warning

Proventeq Content Suite and OpenText eDocs database should be hosted on the same SQL Server instance.

Source System
ot OpenText eDocs 

Name *


Server *
localhost


Use Integrated Security

Username *

Password *

Database Name *

File location 

Timezone 

Name: Name of connection, to uniquely identify the connection within the workspace.

Server: Name of SQL server hosting EDocs database.

Use Integrated Security – If selected then the account currently logged into will be used to access the EDocs database.

Username and password: If **Use Integrated Security** is unselected then specify the username and password of an [SQL Login account](#) with access to the EDocs database.

Database Name: Name of EDocs SQL database

File location: Location where EDocs files are stored. If the documents to be discovered are located across multiple file locations this can be customised by Proventeq with Premium Support or Professional Services.

4.1.10. Adding M-Files Source

Add Source Connection x

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#) 

Source System
M MFiles ▼

Name *

Server Url *

Port Number *
 2266

User Name *

Password *

COM API Connection Type ▼

Test Connection
Add

Name: Name of connection to uniquely identify the connection within the workspace.

ServerUrl: URL of the source M-Files server.

Port Number: Port number for the COM API utilization

Username: Username for connecting to M-Files server. The user should be an administrator for the source M-Files system.

Password: Password for the above-mentioned user.

COM API Connection Type: HTTPS or TCP connection.


4.1.11. Adding Oracle UCM Source

PCS support migrations from Oracle UCM that use either Microsoft SQL or Oracle as their underlying database.

Add Source Connection

A source connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#) 

Source System

Oracle UCM (10G) 


Name *

Server Url *

User Name *

Password *

Use UCM Profiles

Source Database 

Name: Name of connection to uniquely identify the connection within the workspace.

Server Url: URL of the source Oracle UCM server. e.g.

<http://ucmsys.acmecorp.com/16200/dav/cs/idcplg>

Username & Password: Credentials of account with Oracle UCM access

Use UCM Profiles –

Oracle UCM using SQL Server

Source Database
SQL Server

Host Server *

Database Name *

Port *

Use Integrated Security

User Name *

Password *

Sql Schema *

Host Server: Name of SQL database server hosting Oracle UCM database.

Name of Oracle UCM database:

Port: Port number used by SQL server

Option to use Integrated Security. If selected the PMA service account (i.e. the account it runs under will be used to access SQL. If not selected, then required to specify details username and password of a SQL login account with access.

SQL Schema: e.g. dbo

Oracle UCM using Oracle Database

Source Database

Oracle

Host Server *

Port *

SID Service Name

Service Name *

User Name *

Password *

OCS Schema

Host Database Server: Name of Oracle database server hosting Oracle UCM database.

Port: Port used by Oracle database server

Whether to use SID or Service Name

SID/Service Name:

Username & Password- Details of account with access to Oracle UCM database.

OCS Schema:

4.2. Add a New Target Connection

Items are migrated to the system specified by a target connection. When creating a target connection relevant credentials and details of where to migrate to will be required.

Adding a new target connection can either be done from the Migration Job creation wizard or from the Connections option displayed in the Navigation Panel. The target systems shown is determined by the PCS licence that has been applied. Often it will be by a single target.

Add Target Connection

A target connection allows you to specify the type and connection details for a target you wish to migrate to. [Learn more](#)




FIGURE 12 - SELECTING TARGET SYSTEM TYPE

4.2.1. Adding SharePoint Online Target

For more information on authentication options see [Accessing Microsoft 365 from PMA – Proventeq Migration Accelerator](#).




FIGURE 13 - SHAREPOINT ONLINE CONNECTION DETAILS

The following fields need to be configured for a SharePoint Connection:

- **Name:** Name of connection to uniquely identify the connection
- **Connect To:** Select **Tenant** or **Site Collection**.
- **SharePoint URL:** The SharePoint Tenant, Site collection or Team URL

Connect To: Tenant or Site Collection

- **Site Collection** – To migrate to a particular site collection.
- **Tenant** – A Tenant is the parent of all Site Collections. This Tenant option can be used when there is a need to migrate data into more than one Site Collection or when

migrating data to OneDrive. Details of the specific Site Collection within the Tenant to migrate to can be specified in the Migration Job Creation wizard or later, using Structure Mapping feature. Note the tenant role SharePoint Administrator(SPAdmin) is required when using this option to allow it to see across all Site Collections.

SharePoint URL:

When connecting to SharePoint the URL should be as follows

Target	Connection URL format
Root Site Collection	https://<tenancyname>.sharepoint.com
Specific Site Collection	https://<tenancyname>.sharepoint.com/sites/<Site Name>
Team Site	https://proventeq365.sharepoint.com/teams/<Site Name>
Tenant	https://<tenancyname>-admin.sharepoint.com

SharePoint Authentication Methods

There are several authentication methods that can be used to connect to SharePoint

- **SharePoint Online – App Based Authentication** (recommended)
- **SharePoint Online - Client Id Authentication**
- **SharePoint Online - Admin Credentials Authentication**

SharePoint Online – App Based Authentication


The general recommendation is to use App based Authentication whenever possible.

You will need to provide the URL below to your Global Administrator to provide admin consent and return to the application after they have granted consent.

https://login.microsoftonline.com/<TenantID>/adminconsent?client_id=0a8da96c-bf61-4839-9ede-2d0b6647414c

For information on how to get TenantID for your organisation see

<https://docs.microsoft.com/en-us/onedrive/find-your-office-365-tenant-id>



If user is Global admin user, then the user will get a consent screen and user will need to accept the consent.





FIGURE 14 - ACCEPTING APP BASED PERMISSION REQUEST

Tick the checkbox for giving the consent on behalf of your organisation and click on the “Accept” button. This will redirect you back to Add Target Connection screen.

If user is not Global Admin, then user will need to request Admin user to login and accept the consent for Proventeq Migration Accelerator application.



Note: To know more about Azure application permissions and admin consent in Microsoft identity platform endpoint. Please refer the below link:

<https://docs.microsoft.com/en-us/azure/active-directory/develop/v2-permissions-and-consent>

Add Target Connection ✕

A target connection allows you to specify the type and connection details for a target you wish to migrate to. [Learn more](#)

Target System

SharePoint Online

Name *

SPO Site Collection

Migrate to *

Site Collection

SharePoint URL *

https://proventeqdemo.sharepoint.com

Authentication

App Based Authentication
App Based Authentication is Recommended, but Requires Admin Consent.

Client Id Authentication

Admin Credentials

Username *

admin@proventeq.biz

Default User

admin@proventeq.biz

Test Connection
Add

FIGURE 15 - USING APP BASED AUTHENTICATION

App Based Authentication Settings:

- **Username:** The Username for connecting to SharePoint. If connect is to **Tenant** option, then user should be SharePoint Online Admin or Global Admin of the Office365 tenant. If connection is to **Site Collection**, then the user should be a site collection administrator.
- **Password:** The Password for the above-mentioned user.
- **Default User:** The default user to be used for setting Author/Editor fields in the target Site Collection if the source user is not found. This field is optional. See Processing empty source user fields.

Click on the "Test Connection" button, a screen will pop-up to sign into the account of the whitelisted username by Microsoft.

Click on the "Add" button to add the SharePoint connection.

SharePoint Online - Client Id Authentication

Add Target Connection
✕

A target connection allows you to specify the type and connection details for a source you wish to migrate. [Learn more](#)

Target System
SharePoint Online

Name *
SPO Tenant

Migrate to *
Tenant

SharePoint URL *
https://proventeqdemo.sharepoint.com

Authentication

App Based Authentication
App Based Authentication is Recommended, but Requires Admin Consent.

Client Id Authentication

Admin Credentials

Client Id *
04e234da-ce00-46e4-b5a3-7ad4c4ff1c93

Client Secret *
.....

Default User
admin@proventeq.biz

Test Connection

Add

FIGURE 16 - USING CLIENT ID BASED AUTHENTICATION

Client Id Authentication Settings:

- **Client ID:** The app-only principal Client ID.
- **Client Secret:** The app-only principal Client Secret.
- **Default User:** The default user to be used for setting Author/Editor fields in the target Site Collection if the source user is not found. This field is optional. See Processing empty source user fields.

Click on the "Test Connection" button to verify that the details entered are correct.

Click on the "Add" button to add the SharePoint connection.

Note: To set up app-only principal Client ID/Client Secret. Please refer the below link:

<https://docs.microsoft.com/en-us/sharepoint/dev/solution-guidance/security-apponly-azureacs>

SharePoint Online - Admin Credentials Authentication

NOTE: The method of connection below is NOT recommended for production use as it will decrease migration speed due to increased levels of throttling from SharePoint Online.

Add Target Connection

A target connection allows you to specify the type and connection details for a target you wish to migrate to. [Learn more](#)

Target System

Name *

Migrate to *

SharePoint URL *

Authentication

- App Based Authentication
App Based Authentication is Recommended, but Requires Admin Consent.
- Client Id Authentication
- Admin Credentials

Username *

Password *

Default User

FIGURE 17 - USING ADMIN CREDENTIALS AUTHENTICATION

Admin Credentials Authentication Settings:

- **Username:** The Username for connecting to SharePoint. The user should be a site collection administrator for the target Site Collection or SharePoint Online Admin for the tenant level connection.
- **Password:** The Password for the above-mentioned user.
- **Default User:** The default user to be used for setting Author/Editor fields in the target Site Collection if the source user is not found. This field is optional. See Processing empty source user fields

NOTE: When connecting using this method, it's still necessary to use an Application ID to authenticate. By default this will require the PMA Application ID 'd1e5e128-9660-4380-aabb-3e0061c1047c' to be authorised on the tenant. If this is not possible then you may use the Microsoft SPO Management client id instead which is pre-registered on all tenants. This can be done by changing the PmaAppId configuration key as follows:-

```
<add key="SharePoint.PmaAppId" value="9bc3ab49-b65d-410a-85ad-de819febfdcc" />
```

Once configured, the connection will work as the Application ID is already approved.

WARNING: USING THIS APP ID WILL MEAN SPO THROTTLING WILL OCCUR AND SO MIGRATIONS WILL BE SLOWER

Click on the "Test Connection" button to verify that the details entered are correct.

Click on the "Add" button to add the SharePoint connection.

Note: PMA supports migration to GCC (Government Community Cloud). So if the domain is other than ".sharepoint.com" then update the application configuration file typically located here ("C:\Program Files\Proventeq\Proventeq Content Suite\Proventeq.MigrationAccelerator.exe.config"). These keys can be found in the <AppSettings> section.

```
<add key="SharePointOnlineDomainPart" value=".sharepoint.us" />
```

```
<add key="SharepointOnlineAzureEnvironment" value="USGovernment"/>
```

Select Target Connection Path

Select the root path items should be migrated to. The migration target specified here is combined with information in structure mapping to determine the exact location where items will be migrated to.




FIGURE 18 - SELECTING TARGET PATH

4.2.2. Configuration when connecting to Tenant

The following are steps to add a SharePoint Online Tenant as a Target. A Tenant level connection is useful if the migration will be to more than one Site Collection.

If the connect is to Tenant then all the Site Collections in that tenant will be listed below.




FIGURE 19 - CONNECTING TO TENANT

If the Migration is to OneDrive select OneDrive.

Expand to select a collection site

Click on to apply a filter to find the site of interest




FIGURE 20 - FILTERING SITE COLLECTION LIST

NOTE: The selected item can be a specific folder, Document Library, Site Collection or Site. The higher level the node selected then the more information that will need to be specified later in Structure Mapping to specify exactly where data should be migrated to. For example, if no Library is selected here, then that information will need to be provided in Structure Mapping. See

Phase 2 – Structure mapping for more information.

After select the appropriate node, Click **Next** to specify additional job settings

4.2.3. Adding M-Files Target

Add Target Connection

A target connection allows you to specify the type and connection details for a target you wish to migrate to. [Learn more](#)

Target System
✕

M MFiles

Name *

Server Url *

Port Number *
 2266

User Name *

Password *

COM API Connection Type
 TCP

Test Connection

Add

FIGURE 21 - M-FILES TARGET CONNECTION

- Name:** Name of connection to uniquely identify the connection within the workspace.
- ServerUrl:** URL of the target M-Files server.
- Port Number:** Port number for the COM API utilization
- Username:** Username for connecting to M-Files server. The user should be an administrator for the target M-Files system.

Password: Password for the above-mentioned user.


COM API Connection Type: Connection protocol - HTTPS, TCP or gRPC connection.
Selecting gRPC and select port 443 if connecting to M-files cloud.

4.2.4. Adding Azure Storage

Add Target Connection ✕

A target connection allows you to specify the type and connection details for a target you wish to migrate to. [Learn more](#) 

Target System

 AzureStorage ▼

Name *

Connection String *

Field is required

Azure Storage Type

Blob ▼

Test Connection Add

Name: Name of connection to uniquely identify the connection within the workspace.

Connection String: To configure Azure target connection, you will need to enter a Connection String from a Shared Access Signature with these properties as a minimum:-

Allowed services ⓘ

Blob File Queue Table

Allowed resource types ⓘ

Service Container Object

Allowed permissions ⓘ

Read Write Delete List Add Create Update Process Immutable storage Permanent delete

Blob versioning permissions ⓘ

Enables deletion of versions

Allowed blob index permissions ⓘ

Read/Write Filter

Start and expiry date/time ⓘ

Start

End

Allowed IP addresses ⓘ

Allowed protocols ⓘ

HTTPS only HTTPS and HTTP

Preferred routing tier ⓘ

Basic (default) Microsoft network routing Internet routing

i Some routing options are disabled because the endpoints are not published.

Signing key ⓘ

[Generate SAS and connection string](#)

4.2.5. Adding SharePoint 2019

Add Target Connection

A target connection allows you to specify the type and connection details for a target you wish to migrate to. [Learn more](#)

Target System

SharePoint 2019

Name *

Site Collection Url *

User Name *

Password *

Domain Name

Default User

Test Connection

Add

Name: Name of connection to uniquely identify the connection within the workspace.

Site Collection URL: Full URL of target site.

Username and password: Account specified requires Admin rights on the site collection.

Domain Name: Windows domain that the SP2019 system is located in.

Default User: The default user to be used for setting Author/Editor fields in the target Site Collection if the source user is not found. This field is optional. See Processing empty source user fields.

4.2.6. Additional Job Settings

To simplify job creation, settings from other jobs can be copied and applied to this job. These settings are the Structure, Content Type and Security mapping. The following options are available: -

- **Default Settings**

Job is created with default settings, and no information copied from existing jobs. No structure mapping settings or security mapping and only standard Content Type assignments will be configured.

- **Copy settings from file**

In Migration Job Management, the Content Type Mappings and General settings from a job can be exported to files. Using this Copy settings option allows these to be imported. This is especially useful for copying these settings across PMA servers. Custom classifications and security/permission information is NOT copied.


NOTE: This option can only be used between jobs that have the same source and target. i.e. It's not possible to create a job migrating from File Share and use those settings to create a job migrating from Documentum.

- **Copy settings from existing job**

Allows the user to select an existing job to copy Content Type Mappings, Custom Classification and General settings from another job. It will NOT copy any custom content type settings as these are not transferrable between jobs. This option will only be displayed if other jobs have been created.

Job Summary

Before creating the job, review the details shown on the Job Summary screen and alter the job name if necessary.



Job Creation Summary
Summary of source and target connection

Enter Name
Name*
Bramley Office Migration

Source Connection Details
ShareFile Source System
Virtual Root/Personal Folders
Settings
Default settings

Target Connection Details
Bramley Office
<https://doel-my.sharepoint.com/>

After the Migrator Job has been created, you can carry out the next phases of the project to discover information in the source, configure migration settings and migrate data into the target.

← Back **Create Job**

FIGURE 22 - JOB SUMMARY

Clicking **Create Job** will create the job and the Migration Dashboard will be displayed.

5. MIGRATION JOB DASHBOARD

The Migration Job Dashboard allows access to configuration and status information and execution of all migration operations. It is the main screen displayed when a job is selected from Migration Job Management and is also displayed after a job is created using the Migration Job Wizard.




FIGURE 23 - MIGRATION JOB DASHBOARD

5.1. Discovery Status

This section displays information gathered during the Discovery process.

Folders/Containers	Number of folders/containers found
Documents	Number of documents found
Links	Number of shortcuts links found
Other	Any item types not covered by the above types e.g. ShareFile Virtual Collections
Total Discovered Items	Number of items successfully captured during discovery (excludes discovery errors)
Discovery Errors	Number of errors during discovery
Total Size	Total size of items discovered (includes all versions of the items)
Status	Current status of Discovery

5.2. Load Statistics

This section is updated when the **Step 4 Load – Migrate to Target** operation is executed to migrate items into the target.

Documents – Broken down by Migrated, Errored and Pending

Folders – Broken down by Migrated, Errored and Pending

Migration Status	Status from the last migration run
Documents*	Broken down by Migrated, Error and Pending.
Folders*	Broken down by Migrated, Error and Pending
Links	Shortcut links broken down by Migrated, Error and Pending
Total Migration	
Migrated	Total Number of documents and folders that have been migrated
Error	Number of items that have failed migration
Pending	Items yet to be migrated

*When Include Total versions is not selected, if versions of the same item have different processing states it is represented as follows. Any version with Error will count as Error, otherwise any version with Pending will count as Pending, otherwise all versions have to be migrated to count as Migrated.

5.3. Migration Phases


The dashboard displays options organised into the three project phases which control the migration. These will be described in later section.

- Discovery and Analysis
- Migration Preparation
- Migration

For information on other elements of the Migration Dashboard see below.

5.4. Explorer

The explorer feature allows the information gathered during discovery to be easily understood by presenting it as a folder hierarchy which can be expanded to list folders and items.



5.5. Reporting

The reporting option provides access to the following reports.

- Discovery Report
- Embedded Links Report
- Pre-check Report
- Migrated Items Report
- Failed Items Report
- Migration Audit Report
- Performance Report




FIGURE 24 - PMA REPORTS LIST

When a report is displayed the list of reports minimises but the expand open can be used to display them again.

5.5.1. Discovery Report

Displays a list of all items that have been discovered in the source along with additional metadata information and overall status of the item. It's important to review this for correctness and completeness to ensure subsequent steps in the migration process proceed on a sound footing.

Discovery Report [Learn more](#)

back

Current filters: Processing Stage
Total Items: 949

Export (.csv)

Source Item Name	Major Ver...	Minor Ver...	Processing Stage	Extens...	Source URI	Status	Status Message
Virtual Root			Discovery	VirtualCole...	Virtual Root	ⓘ	
Shared Folders			Processing - Load	VirtualCole...	Virtual Root/Shared Folders	✓	Excluded from load, as Merge op
Personal Folders			Processing - Load	VirtualCole...	Virtual Root/Personal Folders	✓	Excluded from load, as Merge op
Stuff I share			Processing - Load	Folder	Virtual Root/Shared Folders/Stuff I share	✓	Excluded from load, as Merge op
Mike Bisborough			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough	✓	Excluded from load, as Merge op
Steve Butler			Processing - Load	Folder	Virtual Root/Personal Folders/Steve Butler	✓	Excluded from load, as Merge op
Migration_Accelerator			Processing - Load	Folder	Virtual Root/Shared Folders/Stuff I share/Migration_Accelerator	✓	Folder already loaded
glossary			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough/glossary	✓	Folder already loaded
Installation_Guide			Processing - Load	Folder	Virtual Root/Shared Folders/Stuff I share/Installation_Guide	✓	Folder already loaded
toc			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough/toc	✓	Folder already loaded
condition			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough/condition	✓	Folder already loaded
test			Processing - Load	Folder	Virtual Root/Shared Folders/Stuff I share/test	✓	Folder already loaded
Adobe Robohelp 2020			Processing - Load	Folder	Virtual Root/Shared Folders/Stuff I share/Adobe Robohelp 2020	✓	Folder already loaded
settings			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough/settings	✓	Folder already loaded
publish			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough/publish	✓	Folder already loaded
variable			Processing - Load	Folder	Virtual Root/Personal Folders/Mike Bisborough/variable	✓	Folder already loaded

FIGURE 25 - EXAMPLE DISCOVERY REPORT

5.5.2. Pre-Check Report

Displays a list of items that have been identified as potential issues by the Pre-Check step. A breakdown of the issues by type appears in the drop down list. Selecting the appropriate Filter will list the items affected by this pre-migration check.

Pre-Check Analysis Report [Learn more](#)

← Back

Current filters: Has Zero Item Size
Total Items: 12

Select a Filter: **Empty Content**

Source Item Name	Issue Type	Count
000003.log	Max Items in Folder	(0 Issues)
000003.log	Links across Multiple Folders	(0 Issues)
000003.log	Mismatch File Names across versions	(0 Issues)
Cookies-journal	Empty Content	(12 Issues)
LOCK	File with no Name	(0 Issues)
Reporting and NEL-journal	Duplicate File Names	(0 Issues)
LOCK	Deleted (or marked for deletion)	(0 Issues)
LOCK	Unsupported version labels	(0 Issues)
LOCK	Max Minor Versions per Major Version	(0 Issues)
000003.log	Temporary File Extensions	(0 Issues)
Cookies-journal	Empty Folders	(2 Issues)
LOCK	Max Major Versions per Document	(0 Issues)

Reporting and NEL-journal | Unknown | C:\Program Files\Proventeq\Proventeq Content Suite\ChromiumCache\Reporting and NEL-journal | C1B103083B95458C586B856404B919C9

5.5.3. Migrated Items Report

Displays a list of all items with a Status of Success

5.5.4. Failed Items Report

Displays a list of all items with a Status of Failed. This is useful to understand issues from a migration and what steps to take to resolve issues.

5.5.5. Error Summary Report

Over several releases, PMA errors have been enhanced to include a error code to simplify error resolution. These are a 3 digit number that will appear in the status message text and can be clicked to perform a search of the PMA support knowledgebase.

For fixed error codes that have occurred in the processing of a task the error summary report will list them and the number of occurrences.


NOTE: Since not all errors currently have a fixed error code, the report also displays a total count of all others errors and more details of them can be seen in the failed items report.

5.5.6. Migration Audit Report

Displays a list of all items in the source, irrespective of processing status. This is a useful way of tracking over migration and often this data is exported and presented to the customer for their records.

5.5.7. Performance Report

Display migration statistics between the specified date period and summarised on hourly or daily basis.



Overall processing rate: 0.401 GB per hour

Start Date	End Date	Total Items	Total Items Size (GB)
6/1/2023 5:00:00 PM	6/1/2023 6:00:00 PM	2205	0.802
6/1/2023 6:00:00 PM	6/1/2023 7:00:00 PM	5	0

Rows per page: 10 | 1-2 of 2

By default periods of no processing will not appear in the table unless the toggle 'Show rows with no processing' is selected.

The overall processing rate (GB per hour) is also calculated and displayed. Time periods for which migration occurs are treated as whole units so for example if processing occurs over a 1 hour period spread across two hours, the hourly rate is based upon 2 hours. With longer processing runs this impacts the overall processing rate calculation less. Selecting the 'show rows with no processing' also affects the overall processing rate calculation because then hours during the time period with no processing are included in the calculation.

5.6. Activity Log

The activity log is accessible from the Menu option and displays the history of job processing. Each time Discovery, Pre-Check or Migration Step are executed the activity log is updated to reflect this.

Process Type	Process Status	Start Time	End Time	Status Message
Capture Metadata	Complete	9 November 2021, 16:09	9 November 2021, 16:09	Pre Migration Check found issues
Capture Metadata	Complete	9 November 2021, 16:09	9 November 2021, 16:09	Pre Migration Check found issues
Classify	Complete	9 November 2021, 15:33	9 November 2021, 15:35	Processing completed
Classify	Complete	9 November 2021, 15:29	9 November 2021, 15:32	Processing completed
Classify	Complete	9 November 2021, 15:10	9 November 2021, 15:10	Processing completed
Classify	Complete	9 November 2021, 15:03	9 November 2021, 15:05	Processing completed
Classify	Complete	9 November 2021, 13:23	9 November 2021, 13:26	Processing completed
Classify	Terminated	9 November 2021, 13:11	1 January 1970, 01:00	Left in inconsistent state
Discovery	Terminated	8 November 2021, 18:42	9 November 2021, 11:17	Cancelled
Capture Metadata	Complete	5 November 2021, 15:57	5 November 2021, 15:57	Pre Migration Check found issues

FIGURE 26 - ACTIVITY LOG

If a migration phase is executed the activity log records the last step as the Process Type, so in the above Classify is the Process Type, even though Capture Metadata step may have also been executed for some/all items.

6. PHASE 1 – DISCOVERY AND ANALYSIS

The Discovery process gathers information for each item contained in the specified source connection. Information gathered includes basic metadata, item version information, location etc. Discovery may take several hours or longer depending upon the amount of data to be captured and the performance of the source system. A filter can be created to limit the data to be discovered. This information is held in the PMA Staging Database and can be viewed from the Items List.

Anything that is to be migrated must be first successfully discovered in this phase. It's therefore vital to ensure Discovery is successful and the results contain all files to be migrated without errors.

This process will help confirm the source data volumes. This can then be used to help determine the number of PMA servers that may be required. It also has an impact on PMA licensing since licenses are volume based and associated with a specific server. For example, if there are several very large Sites Collections it may be recommended to process these on separate more powerful PMA servers so each of these servers would require its own PMA license containing details of the volume that should be migrate.

Note: Discovery only captures basic information on items, it does not capture custom metadata or item content. Only items that are supported by PMA will be captured during discovery.

6.1. Starting Discovery

NOTE: Before starting the Discovery process, it's strongly recommended that all relevant documents are 'checked-in' otherwise such items may not be captured by the discovery process.

Go to  on the Navigation panel to access Migration Job Management and then select the appropriate job.

Job ID	Job Name	Source	Target	Source Path	Target Path	Total Volume	Total Items		
1043	Migration Samples --> insuranceZZ	File System	SharePoint online	C:\Migration Samples	https://dodf.sharepoint.com/insur...	1.02 MB	11	B	o
1037	FileShare to SPO	File System	SharePoint online	C:\Users	https://dodf.sharepoint.com/BadSi...	5.39 GB	206	B	o

FIGURE 27 - MIGRATION JOB LIST

After selecting a job the Migration Dashboard is displayed, Select **Discovery**.

1. Discovery & Analysis Phase [Learn more](#)




FIGURE 28 - PHASE 1 - DISCOVERY




FIGURE 29 - STARTING DISCOVERY

Select **Start Discovery** option to begin the process of capturing information about the source environment into PMA. For many sources, the discovery progress will be displayed in the above screen. For IManage and EDocs, discovery statistics will only be shown at the end of discovery.

After Discovery is complete, the discovery statistics information on the Migration Dashboard will be updated to reflect the information captured during the discovery.






FIGURE 30 - DISCOVERY STATISTICS PANEL

6.1.1. Background Operations

Discovery, pre-check, and migration activities can run as background operations allowing the client still to be used during that time. Select the  button on the Discovery Progress/Migration whilst operation is running. The relevant statistics will be continually

updated on the dashboard and the status will be displayed as **“In Progress”**. Select the  icon to return the full progress screen.




FIGURE 31 - DISCOVERY STATISTICS PANEL DURING DISCOVERY RUN

Only one background operation can execute on the PMA server at any one time. When a background process is running, it will disable options on the dashboard for the current job and all other jobs.

- Discovery – For current and all other jobs, all options available with the exception of Discovery, Pre-check, Migration and Shortcut Links
- Migration – All options disabled within the current job. For all other jobs, Discovery, Pre-check Migration and Shortcut Links are disabled.

The options become enabled as soon as the background operation completes.

6.1.2. Discover Errors

Any failures during discovery will count as discovery errors. Errors can often be at the folder level so even a single discovery error could mean that there are still many 1000’s of items that need to be discovered so it’s essential these errors are understood and resolved if possible.

6.1.3. Filter Discovery Options

Use the **Change Settings** option to control the discovery of security information or apply a filter to what should be discovered. By default, this option is only available when Discovery has not previously been executed. See advanced discovery option in general settings for more information.

Discovery Options

Use options below to control Discovery. [Learn more](#) 

Discover Security Information

Apply Discovery Filter

Filter Criteria

```
[{"ObjectType":"CSV","Filter":"F:\\Proventeq\\Configuration\\Product\\ShareFile\\Discovery Filter.csv"}]
```

FIGURE 32 - DISCOVERY FILTER OPTIONS - EXAMPLE

Discover Security Information

In most cases, this option should be selected but in migrations where all the security information is determined by the target location then this option can be unselected which will improve discovery performance.

6.1.4. Version filtering

For some projects it can be useful to limit the number of versions of documents that are migrated. This can be done at the discovery stage by filtering the number of items discovered. Using this feature it's possible to limit the discovery to just the latest version of each document or the last 'N' versions, where N is a value specified by the user.

This feature is available for ShareFile source.

Delta behaviour when limiting versions.

If a version filter is applied and discovery occurs and the subsequent source item is edited then when discovery is run again, these new version(s) will be discovered, and this will not affect the already discovered items. So for example if version filter is last 3 versions and then a source document is edited twice and discovery re-run then 5 versions of the document will now be in PMA staging database to be migrated.

6.1.5. Discovery Filters

Discovery filters can be applied to limit the information captured during discovery. The filtering capabilities available vary depending upon the source system and whether PMA is configured to use the source system API or not. For example, connecting to Documentum using API provides different filter capabilities if connecting using DB. So, it's important to understand filtering requirements before fully configuring source connection.

For full details of filter capabilities and syntax see. 13.2.

Editing Discovery Filters

By default, after a discovery has begun it's not possible to edit the discovery filter. This is because it can create inconsistent results. For example having no filter and then adding a filter does not remove existing discovered items. Equally removing an entry in the filter does not remove the items from discovery.

However in some scenarios it can be useful to edit the filter, for example to correct a filter value that is specified incorrectly.

Based upon the scenarios above, if editing the filter will not create inconsistent results, then by selecting the Advanced discovery option in General Settings, it allows the Discovery filter to be edited even after discovery has started. Content Technical Support for further information.

6.1.6. Reset Discovery

The **Reset Discovery** option is available after Discovery has been run and may be useful if the Discovery was incorrect and needs to be restarted anew or the size of the staging database needs to be reduced after a migration job has completed the migration. It will remove all existing discovered items, as well as structure, content, and security mappings. It does NOT delete data migrated into the target.

After the reset has completed, the **Start Discovery** option is displayed to allow a new discovery process to be started.

6.2. Delta Migrations

Any modifications to source items after discovery has completed will not be captured unless Discovery is run again. A Delta Discovery/Delta Migration is the term used for additional 'top up/incremental' migrations after the main migration have occurred and may be required when the source system is still active and there is a period between completion of the migration and switch over to the new target.

For example, a migration may take 1 week to run and during that time users are still actively altering the source and so these new documents and edits need to be detected and migrated before switching over.

A Delta discovery run will typically take longer than the original discovery due to the need to gather all information and compare discovery results.

To start a Delta run, select the Discovery option on the Migration Dashboard and select the **Start Incremental Discovery** from the Discovery screen.

Discovery - Migrator Job: Migration to SPO

The Discovery step will connect to source system to capture and record information on each item. Depending upon source system and size, this may take several hours or longer. [Learn more](#)

Last run: 24 February 2022, 10:29




FIGURE 33 - STARTING INCREMENTAL DISCOVERY

The steps for a Delta migration are the same as for the initial migration.

Discovery will identify new/changed/deleted items and pre-check should be run in case any new data fails these checks. In most cases it may simply require a 'review' of the existing settings to review structure mapping, content types and security information.

Finally run the Data Migration and if relevant the Shortcut Links Migration

The table below explains the different delta scenarios and expected results.

Note: It is not recommended to move or rename or re-parent folders and files while migration is underway, as it could lead to lots of duplicate content in target and it will consume additional license utilization.

Delta Scenario	Expected Result
New Folder is added	New Folder would be created on target location.
Folder is modified/renamed	New folder would be created in modified/renamed name and original folder will remain in the same target location which is migrated earlier.
Folder is moved/re-parented to different location	New Folder would be created in moved/re-parent location and original folder will remain in the same target location which is migrated earlier.
Folder is deleted	Folder and contents would not be deleted from target location.
New File is added	New File would be created on target location.
File is modified	File would be updated in delta run
File is renamed	New file will be created with the new name and the original file will remain in the target.
File is moved/re-parented to different location	New file would be created in moved/re-parent location and original file will remain in the same target location which is migrated earlier.
File is deleted	File would not be deleted from target location.
New version is created	New version is uploaded in delta run.
Version is deleted	Version would remain in the target.

6.3. Items List

To launch the Items List, select the Items List menu option or launch from the Discovery dialog box. The Items List will display details of each item captured from the source during Discovery and will be updated by operations executed in the Migration Phase.






FIGURE 34 - LAUNCHING ITEMS LIST FROM DISCOVERY PROGRESS SCREEN

Columns displayed will vary depending upon the source being migrated. Filters can be applied to gain more insight into the data being migrated and cleared using the  icon. Additional columns can be added or removed using the settings icon .

When processing issues occur the details of the error can be found in the Status field.

Processing run: It is possible to filter on **Last Processing Run**.





FIGURE 35 - PROCESSING RUN FILTER

Selecting Last Processing Run will filter the list items to only show items that were processed in some way in the last execution of a migration step.

Export to CSV

The Item List can be exported into a .CSV file using the  option. If a filter is applied to the items list, it will apply to the exported list also. All columns will be exported.

Items List

All items in the source container [Learn more](#)

[← Back](#)

Current filters:
Total Items: 282

Source Item Name	Processing Stage	Exten...	Source Parent Name	Target Parent Name	Target Item Na...	Source URI	Target UR
Users	Discovery	Folder				C:\Users	
Administrator	Discovery	Folder	Users			C:\Users\Administrator	
MSSQLSERVER	Discovery	Folder	Users			C:\Users\MSSQLSERVER	
Public	Discovery	Folder	Users			C:\Users\Public	
SQLTELEMETRY	Discovery	Folder	Users			C:\Users\SQLTELEMETRY	
.azuredatstudio	Discovery	Folder	Administrator			C:\Users\Administrator\azuredatstudio	
Desktop	Discovery	Folder	MSSQLSERVER			C:\Users\MSSQLSERVER\Desktop	
Documents	Discovery	Folder	Public			C:\Users\Public\Documents	
Desktop	Discovery	Folder	SQLTELEMETRY			C:\Users\SQLTELEMETRY\Desktop	
Contacts	Discovery	Folder	Administrator			C:\Users\Administrator\Contacts	
Documents	Discovery	Folder	SQLTELEMETRY			C:\Users\SQLTELEMETRY\Documents	
Desktop	Discovery	Folder	Administrator			C:\Users\Administrator\Desktop	
Documents	Discovery	Folder	Administrator			C:\Users\Administrator\Documents	
Documents	Discovery	Folder	MSSQLSERVER			C:\Users\MSSQLSERVER\Documents	
Downloads	Discovery	Folder	Public			C:\Users\Public\Downloads	
Downloads	Discovery	Folder	Administrator			C:\Users\Administrator\Downloads	
Downloads	Discovery	Folder	SQLTELEMETRY			C:\Users\SQLTELEMETRY\Downloads	

FIGURE 36 - ITEMS LIST

6.3.1. Item level information

Select the item to display the Item Details screen.

Item Details

Item Name: roofrack.jpg

Last processed stage	Discover	Entity Type	File
Status	✓	Processing Stage	
Status Message		Migration Task Id	1033
Id	10746	Descendent Min Processing Stage 10	
Group ID	st33f779-4bbe-48a2-9441-40ff4585baa3	Id	
Status		Last Processing Run Id	
Extension		Minor Version	
Last Processing Date		Major Version	
		Ordinality	1

Source Item

Item Name	roofrack.jpg
Content Type	File
Parent Name	
Url	
Content Type Id	
Item Id	67015
Parent Name	
Content Item Id	fi8705d8-63f2-bcff-384d-1a209249db92
Parent Item Id	67004

Captured metadata

Metadata information will become available after Processing - Extract stage.

Target Item

Item Name	
Content Type	
Parent Name	
Url	
Content Type Id	
Item Id	
Parent Name	
Content Item Id	

Target Metadata

Metadata information will become available after Processing - Transform stage.

FIGURE 37 - EXAMPLE ITEM DETAILS

As an item moves through various process stages then additional information will appear as show in the table below.

6.3.2. Items Details

The following table lists all available columns, * indicates additional columns to **Summary** view.

Column	Description	Possible values	Stage Populated	Notes
Source Content Item ID	This identifies an individual document version in source.		Discovery	
Target Content Item ID	This identifies an individual document version in target.		Load	
Group ID	This identifies an individual document.		Discovery	The same document with several versions will have the same Group ID
Source Item Name			Discovery	

Major Version	e.g. If document version was 10.5 this would be 10		Discovery	
Minor Version	e.g. If document version was 10.5 this would be 5		Discovery	
Processing Stage		Discover – Information gathered by Discovery Capture Metadata - Step 1 of Migration process executed Classify – Step 2 of Migration process executed Transform – Step 3 of Migration process Load – Step 4(final step)	Discovery and Migration Phase	
Source Parent Name			Discovery	
Target Parent Name			Transform	
Target Item Name			Transform	
Extension			Discovery	
Source Url			Discovery	
Target Url			Transform	
Status			Migration Phase	
Source Content Type	This will contain either the content type assigned to the item by the source OR the a Customer Content Type assigned through custom classification		Classify	
Target Content Type*			Transform	
Ordinality	This represents the order in which versions items will be migrated		Discovery	This represents the order in which versions items will be migrated
Entity Type			Discovery	
Status Message				
SourceContentTypeId			Classify	
TargetItemId			Classify	

6.3.3. Source Virtual Collections


The items list may also contain items which don't physically exist in source but are captured in Discovery to represent the source hierarchy. For example, when discovering all the personal folders in ShareFile, a root item will be created in items list for "Personal Folders", which will act as the parent item for individual personal folders. Such items will have a source Entity Type of "VirtualCollection".

6.3.4. Target Structure Entries

As well as source items, some additional entries may appear in the items list termed 'Target Structure Entries'. They are added to represent structural elements that may need to be created by PMA during the migration. So for example if a SharePointLibrary needs to be created in target for splitting source folder hierarchy across libraries , an entry for this will also appear in the Items List so that the success or otherwise of that can be displayed. These items can be identified as they will have "StructureMapping" as the source ItemName.

6.3.5. Processing History

The details of an item being processed can be viewed from the Processing History tab on the Item Details screen.

Item Details [Learn more](#) 

Details		Processing History			
Start Time	End Time	Status Code	Status Message	Processing Run ID	Target Item ID
30 January 2023, 04:32	30 January 2023, 04:33	0	File created successfully.	6	153

FIGURE 38 - ITEM PROCESSING HISTORY

6.4. Pre-Checks

Migrations between different sources and targets often have incompatibility issues due different capabilities, limitations and behaviours in the target which could impact the migration.

The Pre-check option allows a set of checks against the source data to be executed, based upon the known limits of SharePoint. Each can be enabled/disabled and some have additional configuration parameters which can be customised as required.

NOTE: Migrations will still be attempted for items that are reported as potentials issues in the Pre-check. This is why it's important to review and correct as necessary to ensure the successful migration of items.

NOTE: The nature of pre-checks means that if Discovery is halted before completion then pre-check results may be inconsistent and cannot be relied upon.

Pre-check – Migrator job: Migration to SPO

Pre-check will analyse the data captured by Discovery to identify potential incompatibility issues with the target system. [Learn more](#)




FIGURE 39 - STARTING PRE-CHECKS

6.4.1. Changing Pre-Check Settings

The ‘Change Settings’ option displays the options below and allows the checks to be enabled/disabled as well as specifying any relevant values.

Restrictions:

Restrictions are issues that may prevent the folder or file actually being migrated. So for example, because they contain characters in the filename which the target will not allow.

Migration Pre-Checks

Select the options below to check for potential issues with the data in your migration source. Results will be presented in you Power BI report.

FIGURE 40 - PRE-CHECKS – RESTRICTIONS

Blocked Characters in Filenames:

Description: Checks for illegal characters in Source file/folder.

Impact: Items will be migrated but will contain replacement character as specified in General Settings.

Resolution steps: Use General Settings to assign a character to replace any invalid characters.

Invalid or Blocked File Types:

Description: Checks if file type of item is on the blocked file types list. Default list is empty as SharePoint currently supports all File types.

Impact: Items would fail migration but currently N/A.

Resolution steps: Exclude items from migration or convert to supported file type if applicable.

Temporary file Extensions:

Description: Checks for files with specified file type that is considered a temporary file extension and so is likely something that does not require migration. Use comma separated list to provide multiple file extensions.

Impact: Items would be migrated.

Resolution steps: Contact Technical Support.

Limitations

These are limitations in the Target that may prevent the folder/file being migrated. Unlike restrictions, limitations are those that are only an issue once a value exceeds the defined threshold based upon the limits of the target.

Migration Pre-Checks

Select the options below to check for potential issues with the data in your migration source. Results will be presented in the Power BI report.

temporary file extension

Limitations

<input checked="" type="checkbox"/>	Max File Size	<input type="text" value="2000"/>	MB ▾
<input checked="" type="checkbox"/>	Max Characters in Filename	<input type="text" value="128"/>	
<input checked="" type="checkbox"/>	Max Characters in Folder Name	<input type="text" value="256"/>	
<input checked="" type="checkbox"/>	Max URL Length for Items	<input type="text" value="400"/>	
<input checked="" type="checkbox"/>	Max URL Length for Containers	<input type="text" value="400"/>	
<input checked="" type="checkbox"/>	Max Items in Folder	<input type="text" value="5000"/>	
<input checked="" type="checkbox"/>	Max Major Versions per Document	<input type="text" value="500"/>	
<input checked="" type="checkbox"/>	Max Minor Versions per Major Version	<input type="text" value="500"/>	

FIGURE 41 - PRE-CHECKS – LIMITATIONS

Max File Size:

Description: Checks whether the file size exceeds the maximum file size for SharePoint/SharePoint Online.

Impact: Items will fail migration.

Resolution steps: Migrate manually or exclude from migration.

Max characters in Filename:

Description: Checks whether the length of item name exceeds the SharePoint/SharePoint Online limits.

Impact: Items will fail migration.

Resolution steps: Rename source item or rename during migration by setting up a rule for item name mapping. See Populating Target using Functions where you can use functions to trim fields.

Max characters in Folder Name:

Description: Checks whether the length of folder name exceeds the SharePoint/SharePoint Online limits.

Impact: Items will fail migration

Resolution steps: Reorganise folders in source, use structure mapping or contact technical support for assistance.

Max URL Length for Items:

Description: Checks whether the length of a parent container exceeds SharePoint limits.

Impact: Items will fail migration.

Resolution steps: Contact Technical Support.

Max URL Length for Containers:

Description: Checks overall URL length

Impact: Items will fail migration.

Resolution steps: Rename item(s) in source, rename during migration by setting up a rule for item name mapping or shorten the path during migration by using structure mapping.

Maximum Items in Folder:

Description: Checks whether the folder contains more items than permitted within SharePoint Online Document Library folders.

Impact: Items will fail migration once target item limit reached in folder

Resolution steps: This can be resolved either by restructuring data in the source or through structure mapping during migration.

Max Major Versions per Document:

Description: Checks for number of major versions per item since SharePoint has a limit on the number of major versions supported.

Impact: Items will fail migration.

Resolution steps: Contact Technical Support

Max Minor Versions per Major Version:

Description: Checks for number of minor versions per major version since SharePoint has a limit on the number of minor versions supported.

Impact: Items will fail migration.

Resolution steps: Contact Technical Support

Duplication

Any duplication or empty files that may not get migrated into the Target

Duplication



FIGURE 42 - PRE-CHECKS – DUPLICATION

Duplicate file names:

Description: Checks if there are items in the source dataset with the same name

NOTE: Unlike other pre-checks, this check can take several hours to run in larger environments. E.g. 8 hours in an environment of several million items.

Impact: Items will fail migration unless one of the resolution steps below is used.

Resolution steps: In General Settings, Duplication there is the option “Create a new file with a unique name” to control the migration of duplicate named items and provide a unique name as required (by default this is enabled). Alternatively, restructuring the source system and rerun discovery or resolve the conflict using structure mapping.

Files with no name:

Description: Checks whether the Item Name field is blank.

Impact: Items cannot be migrated

Resolution steps: Edit source item or create a function mapping to assign value. See Populating Target using Functions where you can use functions to apply a name in such scenarios.

Deleted (or marked for deletion):

Description: Checks whether the item is marked as deleted in the Source system.

Impact: Items that have been deleted/marked for deletion will still be migrated.

Resolution steps: Contact Technical Support

Empty content (Zero Byte):

Description: Checks whether the Item size is zero bytes as this could indicate issue with the source system

Impact: Items will fail migration.

Resolution steps: Items should be examined by a record officer/system administrator to determine whether the files truly are missing. If so, the issue can be worked around by loading placeholder content using the "LoadPlaceholdersForMissingOrEmptyFiles" advanced setting.

Empty Folders:

Description: Checks for folders with no content. By default this check is OFF and so not executed.

Impact: Empty folders will be migrated.

Resolution steps: Review the list to see if such folders should be excluded from migration. By default such items will be migrated but the configuration key FilterEmptySourceFolders can be set to True so empty folders are not migrated.

Other Checks

Other properties that may prevent **migration into the Target**.

Other Checks



FIGURE 43 - PRE-CHECKS – OTHER CHECKS

Mismatch File Names across versions:

Description: Checks whether the versioned items having different file names. I.e. version 1 of a file is called Dept Training.docx and version 2 is called Dept Training(Old).docx. In SharePoint, all versions of the file must have the same name.

Impact: Items will be migrated and by default will have the same name as the first version

Resolution steps: For steps on how to use information from the latest version across all versions contact Technical Support

Mismatch File Names or Extensions across versions:

Description: Checks whether the filename or file extension of an items changes across versions of the item. SharePoint requires all names and extensions to be the same for all versions.

Impact: Items will be migrated and by default will have the same name/extension as the first version.

Resolution steps: For steps on how to use information from the latest version across all versions contact Technical Support

Links across Multiple Folders:

Description: Detects if source system has Shortcut links. In the Power BI report, these are labelled as content referenced by multiple folders.

Impact: Shortcut links need to be migrated if required.

Resolution steps: If Shortcut Links need to be migrated, ensure “Links” source content type is configured correctly in Content Type mapping and run Shortcut Links migration, after all items are successfully migrated.

Content type Mismatch Across Versions:

Description: Checks whether the Content Type/Category/Classification for all versions of a document are the same. Since SharePoint requires all version to be of the same Content Type.

Impact: Items will fail migration.

Resolution steps: Contact Technical support

Unsupported version labels:

Description: SharePoint online supports version labels like 1.1, 2.3 etc. Some source systems supported version labels such as 2.3.1 or even text label so such issues will be detected with this check.

Impact: Items will fail to migrate

Resolution steps: Contact Technical support

6.4.2. Running Pre-Checks

Select **Discovery & Analysis Phase->Pre-Checks** option and then select the Start Pre-checks. The checks normally take several minutes to execute.

6.4.3. Review and correcting pre-check issues

There are two ways to view pre-check results.

Power BI Report

Once the pre-check is complete, the number of potential issues will be displayed. Clicking on the 'View Report' will launch PowerBI to display the results. There are several pre-check related tabs which contain the results of each check. In general, any checks which return a result of 'True' are issues to be investigated.

Two warnings are displayed when opening Power BI

1. Potential security risk

Displays warning about 'Potential security risk' due to the file using multiple data source. Click **OK** to continue.

2. Native Database Query

Displays warning to approve running native query. Click **Run**

PowerBI will open up to display the Content Summary dashboard. Select the Pre-Check General tab to view the total number of issues.




FIGURE 44 - TOTAL PRE-CHECK ISSUES

The result may be highlighted in amber to suggest a Informational/Warning as opposed to a failure. An example of this is the 'Empty Folders' warning.




FIGURE 45 - EXAMPLE OF PRE-CHECK WARNING




FIGURE 46 - EXAMPLE F PRE-CHECK ERRORS

In this example of an error, 17 items have file extensions not allowed in the target.

Pre-Check Report

There is a pre-check report available and a drop down list of issues and the number of items impacted will be displayed.

Pre-Check Analysis Report [Learn more](#)

← Back

Current filters: Has Zero Item Size

Total Items: 12

Source Item Name	Issue	Count
000003.log	Max Items in Folder	(0 Issues)
	Links across Multiple Folders	(0 Issues)
	Mismatch File Names across versions	(0 Issues)
Cookies-journal	Empty Content	(12 Issues)

Select a Filter: Empty Content

FIGURE 47 - PRE-CHECK FITER

7. CREATING DETAILED MIGRATION PLANS

7.1. Introduction

The completion of the Discovery Phase is an important milestone and provides the essential information necessary to help create a more detailed migration plan. Here are some of the key considerations when planning a migration.

- Performing pilot/smaller scale migrations to validate migration configuration and understand performance to help identify any changes that may be required in the environment, including adding additional PMA servers.
- Understanding business priorities and data volumes to help determine the order of the migration.
- Initiate User Acceptance Testing (UAT) planning.

Delta Migration

If the source system is still active, then after an initial migration, customers may execute a 'top up' or otherwise known as a 'delta migration'. In this way, the bulk of the data is migrated, and the delta migration allows any subsequent updates that occurred on the source to also be migrated. Note that in such cases, the target is overwritten so it's important for users to understand this and only make and changes to documents in the source platform. For more information on Delta Migrations see [Delta Migrations](#).

7.1.1. Content Type Planning

- Creating new Target Content Types

There may be source content types that have no current equivalent in the target and so decisions need to be made as to whether they should be mapped to an existing target content type or whether a new content type is created in the target.

Once these content types are created in the target then they can be mapped to using the Content Type Mapping feature.

- Mapping several source Content Types to single Target Content Type

In some migrations, customers may wish to simplify the existing content types and so map several different content types in a source to a single content type in the target.

- Separating single content type into many target content types

There can be scenarios where a single source content type needs to be separated out into more than one target content type. PMA allows the creation of 'Custom Content Type' and allows the user to define criteria using the metadata of the item to identify them as a particular content type which can then be mapped to a suitable target content type. See [Custom Classification](#) for more details.

- Sign off on metadata mapping

It's essential that all source fields are understood for all contents types so that metadata mapping is correctly configured and signed off to move the data to the target.

7.1.2. Structure Mapping

Each of the existing source locations needs to be reviewed and as applicable, the target location for these needs to be determined as part of this planning process. See

Phase 2 – Structure mapping for more details.

When designing target layout be aware of limitations in SharePoint that may create performance issues. See also:-

<https://support.microsoft.com/en-us/topic/cf37b449-a2a7-4ef9-9f4d-aab826db5b30> - Understanding and managing large lists.

<https://docs.microsoft.com/en-us/office365/servicedescriptions/sharepoint-online-service-description/sharepoint-online-limits> for more information on SharePoint Online limits.

7.1.3. Security

The security mapping will export lists of users, groups and permissions that may need to be mapped. See Security Mapping for more details.

Decision on what User in the target system should items be associated with if the source user is not in the target system e.g. Leavers

It is strongly recommended to review/simplify permissions as part of the migration. For example, putting permissions on the SharePoint Libraries and Folders rather than at an individual item level due to SharePoint limitations as SharePoint only allows 50,000 unique permissions in a single library.

7.1.4. Shortcut Links/Embedded Links processing

Decision on whether to migrate shortcut links from source to target. Note Shortcut Link migration occurs after all source items are migrated and is a much slower process.

Decision to convert links embedded within documents to resolve to new locations. This will also significantly impact migration performance. Note: Password protected/encrypted items cannot be processed.

Phase 2 – Structure mapping

Structure Mapping is used to define where the source folders/containers are migrated to in the target. The location details in the Target Connection are combined with the information here

to allow the full location to be determined. It is one of the key elements within the Migration Preparation phase following on from successful Discovery and detailed planning.

It's important to bring this information and an understanding of the target and requirements of the business and end users to create a set of rules, to ensure data is migrated to the correct target location.




FIGURE 48 - PHASE TWO – STRUCTURE MAPPING OPTIONS

There are three structure mapping options that may be available depending upon the exact target location specified. See Add a New Target Connection

- **Recreate using Source Hierarchy**

This will create the source folders below the specified target location in the migration job. This option is only available when the target location is a Document Library or Folder and the source location is also a folder.

- **Restructure using Folders/Containers**

This feature allows folders to be reorganized during the migration by 'mapping' source containers to target containers. The assignment between source and target containers is done using a .CSV file which can be download and then imported after editing.

- **Restructure using Item Metadata**

Metadata structure mapping is a feature whereby the target location for items is based upon customer written rules that use source item metadata properties. The assignment between source item metadata and target folders is done using a .CSV file which can be download and then imported after editing.

Note: To update any structure mapping entries, it's necessary to first delete the existing structure mapping before then importing new mappings.

Once any items have been processed in the Migration phase then it's not possible to alter the structure mapping. To alter the mapping, it's necessary to use the Undo option which will first delete any migrated items and provides the option to undo the current structure mapping.

7.2. Recreate using Source Hierarchy

Selecting this option will create a folder hierarchy in the target by creating the existing source folder/container hierarchy beneath the location specified in the Target.

The existing hierarchy in the source will be used in the target.

This option is only available if a Document Library or folder has been selected in the target connection since then no additional information is required to migrate the existing source hierarchy into these.




FIGURE 49 - RECREATE USING SOURCE HIERARCHY

- **Merge into Existing Folder Option**

Recreate structure mapping has the **Merge** into Existing folder option. By default, items will be migrated into the folder specified in the target. If unselected, then the final folder path specified in the source of the items will be used to first create a 'root/parent' folder beneath which the items will then be migrated. See TargetRootSettin

7.3. Restructure using Folders/Containers

Using this feature the customer can create a table called a '**Structure Mapping**' which lists source folder/containers and specifies where they should be placed in the target. When an entry is specified, all of its children will also be moved beneath it, so it's not necessary to specify all source folders.






FIGURE 50 - RESTRUCTURE USING FOLDERS/CONTAINERS

In summary the process is to download source system structure information into a .CSV file. Edit this to add suitable target details and then upload the .CSV file.

Select the download  icon to start Structure mapping. The .CSV file to be used to populate structure mapping will be populated list of folders from the source. When download option is selected, the user is prompted for the folder path depth. This is the number of folders ‘down’ that it should export. Note the value is relative to the source path specified.



Example Source Folder Hierarchy:

```
Documents\Engineering\Project Diamond
Documents\Engineering\Project Diamond\Documentation
Documents\Engineering\Project Diamond\Beta Programme
Documents\Engineering\Project Diamond\Beta Programme\Internal
Documents\Engineering\Project Diamond\Beta Programme\SE Community
Documents\Engineering\Project Diamond\Beta Programme\External
```

Specify a folder depth of three would populate the CSV with unique folders that are 3 levels deep .

Folder Depth of 3

```
Documents\Engineering\Project Diamond
```

Folder Depth of 4

```
Documents\Engineering\Project Diamond
Documents\Engineering\Project Diamond\Documentation
Documents\Engineering\Project Diamond\Beta Programme
```

7.3.1. SharePoint Structure Basics

This section describes the basic principles of structures in SharePoint and may be helpful if the user is not very familiar with SharePoint.

The structure to locate any item in SharePoint is defined by 3 elements

- SiteCollection
 - Document Library
 - Folder

Items can be stored at the Document Library level (i.e. the root) or within a Folder or Subfolder.

To migrate into SharePoint the SiteCollection, Document Library and Folder needs to be known. Depending upon the information specified in the Migration Job, all of this information may have been specified, if not, then the omitted fields need to be specified in Structure Mapping to allow these items to be migrated successfully.

7.3.2. Completing Structure Mapping Overview

Source related fields in Structure Mapping (SourcePathID and SourcePath)

Depending upon the source. Structure mapping will either require the SourcePath or SourcePathID to be specified to identify the source location to be mapped depending upon the source. These columns will be populated automatically when the structure mapping template is downloaded.

Target fields in Structure Mapping

The information that's mandatory in structure mapping depends upon the full target path specified when the migration job was created. e.g. If a Site Collection was specified as the target location in the Migration Job, then TargetSubSite, TargetLibrary are required and TargetFolder is optional. (The folder names in the target will come from the source).

1	SourcePathID	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
2		E:\FileSystem Test Data\Insurance		/	Insurance	/	Create
3		E:\FileSystem Test Data\Insurance\Health Insurance		/	Insurance	Health	Create
4		E:\FileSystem Test Data\Insurance\Car Insurance		/	Insurance	Car	Create
5		E:\FileSystem Test Data\Insurance\Travel Insurance		/	Insurance	Travel	Create
6		E:\FileSystem Test Data\Insurance\Health Insurance\Claims		SubSite	Claims	Health/Claims Docs	Create
7		E:\FileSystem Test Data\Insurance\Car Insurance\Claims		/	Claims	Car/Claims Docs	Create
8		E:\FileSystem Test Data\Insurance\Travel Insurance\Claims		/	Claims	Travel/Calims Docs	Create
9		E:\FileSystem Test Data\Insurance\Insurance Archive		Archive	Archive	Archive Docs	Merge
10		E:\FileSystem Test Data\Insurance\Others		Archive	Archive	/	Create

FIGURE 51 - EXAMPLE STRUCTURE MAPPING FROM FILE SHARE

Structure Mapping Field	Description
TargetSiteCollection	This is a URL that is required when:- A: Target path is to tenant level. B: To migrate to a Site Collection other than what's specified in target path.
TargetSubSite	Specify / to migrate to root, otherwise the name of the SubSite. If the SubSite does not exist, it will be created using the Team Site template.
TargetLibrary	Required if a Document Library is not specified in target path on the Migration job.
TargetFolder	Not mandatory. Specify if want to migrate to specific folder.

TargetRootSetting	Required if wanted to use MERGE setting.
--------------------------	--

FIGURE 52 - STRUCTURE MAPPING VALIDATION

When a structure mapping is imported, it will be validated using the logic from the above table to ensure that columns contain necessary values. With the exception of the TargetRootSettings field, it does NOT ensure that the values are correct/exist in the target.

Target SiteCollection

This is the **Full URL** of the Target Site collection.

Target SubSite

Specify / to migrate to root, otherwise the name of the SubSite. If the SubSite does not exist, it will be created using the Team Site template.

Target Library

If migrating to an existing library, the value needs to be the 'internal name' of the target library NOT the display name e.g. Shared Documents (Internal name) instead of Documents (Display Name). Note values are **case sensitive so specify the internal name exactly**. If the specified library does not exist, it will be created.

TargetFolder

Specify / to migrate to the root folder or else specify name of folder which will be created if it does not exist. Any value specified will overwrite the target folder.

TargetRootSetting

If TargetRootSetting field is blank or set to **CREATE**, the final folder path in the source path will be used to create a parent root folder in the target underneath which the data is migrated. A value of **MERGE** can be specified and in that scenario no root path is created and the data is migrated directly into the target folder.

7.3.3. Structure Mapping Examples

Structure Mapping example files are located in C:\Program Files\Proventeq\Proventeq Content Suite\SampleFiles

Example File Share Structure Mapping

	SourcePathId	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
1		E:\FileSystem Test Data\Insurance		/	Insurance	/	Create
2		E:\FileSystem Test Data\Insurance\Health Insurance		/	Insurance	Health	Create
3		E:\FileSystem Test Data\Insurance\Car Insurance		/	Insurance	Car	Create
4		E:\FileSystem Test Data\Insurance\Travel Insurance		/	Insurance	Travel	Create
5		E:\FileSystem Test Data\Insurance\Health Insurance\Claims		SubSite	Claims	Health/Claims Docs	Create
6		E:\FileSystem Test Data\Insurance\Car Insurance\Claims		/	Claims	Car/Claims Docs	Create
7		E:\FileSystem Test Data\Insurance\Travel Insurance\Claims		/	Claims	Travel/Calims Docs	Create
8		E:\FileSystem Test Data\Insurance\Insurance Archive		Archive	Archive	Archive Docs	Merge
9		E:\FileSystem Test Data\Insurance\Others		Archive	Archive	/	Create
10							

FIGURE 53 - EXAMPLE STRUCTURE MAPPING FROM FILE SHARE

In this example, assume that the SiteCollection has been specified as **AcmeSure** in the Target Connection in the Migration Job. This means it is not required in the structure mapping. This is a FileShare migration and so the SourcePath field is used to specify the source path. By using the download structure mapping template feature the SourcePath will be prepopulated.

Row 1

- TargetSubSite is set to / since not migrating to a Subsite
- TargetLibrary contains name of Document Library **Insurance**
- TargetFolder is set to / to migrate to the root of the Insurance Document Library
- TargetRootSetting is set to **Create**. This means the last folder Path in SourcePath will be created as a root.

Result: -

Items in “E:\File System Test Data\Insurance” are migrated to “AcmeSure\Insurance\Insurance”

Row 2

As above but TargetFolder is specified so items from Health Insurance folder in the Source are migrated to **Health** folder with the Insurance DocumentLibrary.

Result: -

Items in “E:\File System Test Data\Insurance\Health Insurance” are migrated to “AcmeSure\Insurance\Health\Health Insurance”

See how the **Create** TargetRootSetting means that the “Health Insurance” folder is created below the Health Target Folder.

Row 9 – Example using MERGE

- TargetSubSite is set to **Archive** so migration is to SubSite called **Archive** which will be created if it does not exist.
- TargetLibrary contains name of Document Library **Archive**
- TargetFolder is set to **Archive Docs** to migrate to the Archive Docs folder (which will be created within the Archive Sub Site if it doesn’t exist)
- TargetRootSetting is set to **Merge**. This means items in the root of the source folder will be migrated into the root of the target.

Result: -

“E:\File System Test Data\Insurance\Insurance Archive” are migrated to “AcmeSure\Archive\Archive\Archive Docs”

Note how because TargetRootSetting is set to Merge, “Insurance Archive” is not in the target path. If it was set to Create, items would be migrated

E:\File System Test Data\Insurance\Insurance Archive migrated to
AcmeSure\Archive\Archive\Archive Docs\Insurance Archive

Below is an example where the Target connection is at the Tenant level and no specific Site Collection is specified so the **TargetSiteCollection** is mandatory as it specifies the Site Collection the items should be migrated to.

SourcePat	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
	FileSystem\Test Data\Insurance	https://demo.sharepoint.com/sites/Insurance	/	Insurance	/	Merge
	FileSystem\Test Data\Insurance\Health Insurance	https://demo.sharepoint.com/sites/Health Insurance	/	Insurance	Health	Create
	FileSystem\Test Data\Insurance\Car Insurance	https://demo.sharepoint.com/sites/Car Insurance	/	Insurance	Car	Create
	FileSystem\Test Data\Insurance\Travel Insurance	https://demo.sharepoint.com/sites/Travel Insurance	/	Insurance	Travel	Create
	FileSystem\Test Data\Insurance\Health Insurance\Claims	https://demo.sharepoint.com/sites/Health Insurance	Claims	Claims	Health/Claims Docs	Create
	FileSystem\Test Data\Insurance\Car Insurance\Claims	https://demo.sharepoint.com/sites/Car Insurance	/	Claims	Car/Claims Docs	Create
	FileSystem\Test Data\Insurance\Travel Insurance\Claims	https://demo.sharepoint.com/sites/Insurance	Claims	Claims	Travel/Calims Docs	Create
	FileSystem\Test Data\Insurance\Insurance Archive	https://demo.sharepoint.com/sites/Insurance	Archive	Archive	Archive Docs	Merge
	FileSystem\Test Data\Insurance\Others	https://demo.sharepoint.com/sites/Insurance	Archive	Archive	/	Create

FIGURE 54 - EXAMPLE STRUCTURE MAPPING FOR FILESHARE WHEN CONNECTING TO TENANT

Example Non FileShare/ShareFile Structure Mapping

For migrations other than ShareFile and File Share, structure mapping entries require that the SourcePathID is used to identify the target path. By using the download structure mapping template feature the SourcePathID will be prepopulated.

SourcePathID	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
D3FCBE579BEC5E526455DB6E6DE2B6CD			/	Insurance	/	Create
05AF79670949F0E3A1224ABE7238EAC8			/	Insurance	Health	Create
E0BA90466FCC529D8CC6ABFF8D64F9B2			/	Insurance	Car	Create
60BA5B81972624E46C48BB6C567F1184			/	Insurance	Travel	Create
87FF02A6C7F26144B5763E476923269F			SubSite	Claims	Health/Claims Docs	Create
656458C6194DDC87C1F2A6F5A6DF8496			/	Claims	Car/Claims Docs	Create
CEC49D75D30181E34FE0056AA8FC3C58			/	Claims	Travel/Calims Docs	Create
783C72F45664A9A07E85FEDC628669E5			Archive	Archive	Archive Docs	Merge
4FC73A3D3FAA9A468F05F515D17325CD			Archive	Archive	/	Create

FIGURE 55 - EXAMPLE STRUCTURE MAPPING USING SOURCEPATHID

SourcePathID	SourcePathType	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
090007c280004646			https://demo.sharepoint.com/sites/Insurance	/	Insurance	/	Merge
090007c280004b17			https://demo.sharepoint.com/sites/Health Insurance	/	Insurance	Health	Create
090007c280004b6c			https://demo.sharepoint.com/sites/Car Insurance	/	Insurance	Car	Create
090007c280005135			https://demo.sharepoint.com/sites/Travel Insurance	/	Insurance	Travel	Create
090007c280004604			https://demo.sharepoint.com/sites/Health Insurance	Claims	Claims	Health/Claims Docs	Create
090007c280004604			https://demo.sharepoint.com/sites/Car Insurance	/	Claims	Car/Claims Docs	Create
090007c280004604			https://demo.sharepoint.com/sites/Insurance	Claims	Claims	Travel/Calims Docs	Create
090007c280004b1c			https://demo.sharepoint.com/sites/Insurance	Archive	Archive	Archive Docs	Merge
090007c280004b19			https://demo.sharepoint.com/sites/Insurance	Archive	Archive	/	Create

FIGURE 56 - EXAMPLE STRUCTURE MAPPING USING SOURCEPATHID WHEN CONNECTING TO TENANT

Example Structure Mapping to OneDrive

When migrating to OneDrive, there needs to be a structure mapping entry for each user. The TargetSiteCollection URL is usually of the form **https://<tenant name>-my.sharepoint.com/personal/<user principal name>**

SourcePathID	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
	-1 Personal Folders	https://acmecorp-my.sharepoint.com/	/	Documents	/	MERGE
foh9eb5c-514c-4946-a18d-a212f2ada3d9	Personal Folders/Percy Shelley	https://acmecorp-my.sharepoint.com/personal/percy_shelley_acmecorp_com	/	Documents	/	MERGE

FIGURE 57 - EXAMPLE STRUCTURE MAPPING TO ONEDRIVE

7.4. Restructure using Item Metadata

This feature allows the target location for items to be based upon rules which use source item metadata properties. For example, documents should go to a folder called 'Financial Records' if the value of a Department property = 'Financial'. In the examples discussed below, only the Target Folder is being assigned for the item, but just like normal structure mapping, the mapping can define Site Collection, Library and Folder within the target.




FIGURE 58 - RESTRUCUTURE USING ITEM METADATA

NOTE: The Pseudo code examples below are not how the rules are structured but serve to explain the capabilities that this feature can provide.

Example 1:

```
IF Department=" Finance" AND CustomerType="Top50"
THEN
    Target Folder="Large Accounts Finance Data"
```

Example 2:

```
Target Folder="All Non Financials" ; (You can define a 'catch all' target folder)
IF Department="Finance" AND CustomerType="Top50"
THEN
    Target Folder="Finance Large Accounts"
ELSE
    IF Department="Finance"
    THEN
        Target Folder="Finance Small Accounts"
    ENDIF
ENDIF
```

NOTE: When using this feature, it's essential to take a two pass approach to the migration. When in the migration phase, first execute **up to Step 3-Transform ONLY**. This will generate the necessary information about the location items will be migrated to. After this has been executed for **all items**, then Step 4 – Load can be executed.

7.4.1. Configuration Steps for Restructuring using Item Metadata

Metadata structure mapping works by defining a ‘Target Assignment Expression’ whose resulting output is examined for a match in the structure mapping table to determine the target to assign the item to.

Configuration Steps:-

1. Specify Target Assignment Expression
2. Populate the structure mapping table with values to compare with the output from step 1 and the target location.

The process to configure it will be explained by the example below.

Step1: Defining Target assignment expression

Scenario: Assign items to Target based upon the value of source metadata field ‘ItemDepartment’. The name of source metadata fields that can be used are visible in Populating Target metadata field form.

Example Target Assignment Expression

```
Department='{ItemDepartment}'
```

Example Source Item Metadata

Item No	ItemDepartment	Result from Expression Evaluation
1	HR	Department ='HR'
2	Finance	Department ='Finance'
3	Security	Department ='Security'

Example Structure Mappings

SourcePath	TargetPath
Department ='HR'	HR Items
Department ='Finance'	Finance Items

When Item No. 1 is processed, during the Transform step, the Target Assignment Expression is read, the value from the metadata field *ItemDepartment* is retrieved and replaces the field name in the expression to generate the result, Department='HR' This is then used to scan for a matching entry in the structure mappings table and a row with the matching value is found so the TargetPath is read and that item is assigned with a TargetPath of “HR Items”.

Similarly for Item No. 2, the result is Department='Finance' and the item is assigned to "Finance Items".

Item 3 would generate a result of Department='Security' but wouldn't find a match in the structure mapping table and so the item would fail to be migrated because no target would be assigned.

In Target Assignment Expressions, the variable name shown in this example 'Department' can be any string, what's essential is that the output from the expression is in the structure mapping table.

NOTE: You cannot use comparators like "<>" nor Boolean operations like "OR" etc. in these Expressions. In these examples comparators = and Booleans like AND are just text to make the expression human readable. It's not the case that they're used during expression evaluation. Target Folders Assignment expressions are simply processed by replacing field labels with actual metadata values and the output value used to find exact matching entry in structure mapping.

7.4.2. Advanced Target Assignment Expressions

Target Assignment expressions support have additional capabilities.

In this second example Finance Items related to Top50 customers goes to Finance Large Accounts, otherwise Finance Items go to Finance Small Accounts. All other items will go to the "All Non Financials" folder.

In the example expression below, the first criteria is based upon two fields and then a second separate criteria is specified after the semi-colon.

Department='{ItemDepartment}' AND CustomerType='{ItemCustomer}';
Department='{ItemDepartment}'

Example Source Item Metadata

Item No	ItemDepartment	CustomerType	Output from Expression
1	HR		Department ='HR'
2	Finance	Top 50	Department ='Finance' AND CustomerType='Top 50';Department='Finance'
3	Security		Department ='Security'
4	Finance		Department ='Finance' AND CustomerType='';Department='Finance'

Example Structure Mappings

SourcePath	TargetPath
Department ='HR'	HR Items
Department ='Finance' AND CustomerType='Top 50'	Finance Large Accounts
Department ='Finance'	Finance Small Accounts

When Item 2 is processed the expression is evaluated and the first element of the output “Department ='Finance' AND CustomerType='Top 50'” is used to lookup on Structure Mapping and so assigns item to TargetPath 'Finance Large Accounts'.

For item 4, the Customer Type is empty so the output from first expression is Department ='Finance' AND CustomerType="" which has no matching entry in structure mapping so the next element of the output Department='Finance' is used for structure mapping lookup and so items are assigned to the TargetPath of Finance Small Account.

Target Assignment Expression order

It's essential to understand that expressions are processed from left to right, so in the above example the more 'specific' criteria is evaluated first. Only if an item doesn't meet the first criteria for 'Department AND CustomerType', is it then evaluated based on Department only.

Example of two expressions in the **WRONG** order.

```
Department='{ItemDepartment}' ; Department='{ItemDepartment}' AND CustomerType='{ItemCustomer}'
```

This is evaluated as: -

Department='Finance' and then

Department='Finance' AND CustomerType='Top50'

In this example every 'Finance' record would always meet the first criteria since it's broader, even though the more specific second rule is what is intended for some items.

7.4.3. Default Target Assignment

When using criteria to assign folders it's possible that some folders may not match any of the criteria specified. To cover this scenario, a 'Default' folder can be assigned to such items. If no 'Default' folder is configured, then these items will not be migrated.

Scenario: Items which don't match any specific values in the structure mapping table should be assigned a specific target location

Effectively this is just a case of creating criteria that is evaluated last of all and will always have a matching entry in the structure mapping table.

Department='{ItemDepartment}' AND Customer='{ItemCustomer}' ;
 Department='{ItemDepartment}';Default

Example Source item metadata

Item No	ItemDepartment	Result of Evaluation
1	HR	Department ='HR'
2	Finance	Department ='Finance'
3	Security	Department ='Security'

In the structure mapping specify in the field SourcePath an entry for Default and a target value.

Example Structure Mappings

SourcePath	Target Folder
Department ='HR'	HR Items
Department ='Finance'	Finance Items
Default	All Non Financials

In this example, when an item that's not in 'HR' or 'Finance' is processed the last entry is processed which is simple the string value of 'Default'. This 'result' is used to scan the structure mapping table and finds a matching entry and assigns the item to that target folder specified. It will always find a match on 'Default' so items from the 'Security' department will be assigned to a target folder of "All non Financials"

Example Metadata_Expressions_Structure_Mapping.csv

SourcePathId	SourcePath	TargetSiteCollection	TargetSubSite	TargetLibrary	TargetFolder	TargetRootSetting
	DEFAULT		/	Insurance	/	Create
	Matter='Insurance' AND SubMatter='Car Insurance'		/	Insurance	Car Insurance	Create
	Matter='Insurance' AND SubMatter='Car Insurance Claims'		Claims	Insurance	Car Insurance/Claims	Create
	Matter='Insurance' AND SubMatter='Home Insurance'		/	Insurance	Home Insurance	Create
	Matter='Insurance' AND SubMatter='Property Insurance'		/	Insurance	Property Insurance	Create
	Matter='Insurance' AND SubMatter='Marine Insurance'		/	Insurance	Marine Insurance	Create
	Matter='Insurance' AND SubMatter='Fire Insurance'		/	Insurance	Fire Insurance	Create
	Matter='Insurance' AND SubMatter='Claims'		Claims	Insurance Claims	/	Merge

FIGURE 59 - EXAMPLE ITEM METADATA STRUCTURE MAPPING

7.4.4. Metadata Structure Mapping Configuration Steps

These are the steps to follow to configure Metadata Structure Mapping.

1-Specify Target Assignment Expression

Select the  option on the Restructure using Item Metadata

Settings

Metadata Expression Match Format:

Save

FIGURE 60 - ENTER ITEM METADATA STRUCTURE MAPPING

Enter the expression as required. e.g.

```
Department='{ItemDepartment}' AND CustomerType='{ItemCustomer}' ;
Department='{ItemDepartment}';Default
```

Once the above file is changed it's essential for the PMA application is restarted.

2-Download Template





FIGURE 61 - DOWNLOADING TEMPLATE FOR ITEM META RESTRUCTURING

Select the **Restructure using Item metadata** and select the  icon to download the template to use.

In the template the evaluated expression result should be placed in the SourcePath column. All other target related columns should be completed as required. See Restructure using Folders/Containers for more information.

Once the structure mapping file is complete, select the **Import** icon to import the file. The contents of the structure mapping will be displayed.

8. PHASE2 – CONTENT TYPES

8.1. Mapping Content Types

For details on what are content types, what is content type mapping see 1.2. Migration Terms and Concepts.

Until a Source Content Type is mapped, items of that type cannot be migrated. Automatic content type mapping will occur for ‘well known’ content types.

In this example there is an unmapped Content Type in the Source named ‘File’. So, we are going to map ‘File’ to a Content Type of ‘Document’ in the Target.

Steps:

Click on Content & Metadata Mapping. The left pane shows **Unmapped Content Types** for the source, the right pane shows **Mapped Content Types**.





FIGURE 62 - MAPPING SOURCE TO TARGET CONTENT TYPE

Click on ‘File’ and click on ‘Document’ in the Target and select the **Map** button. The entry File>Document will appear in the Mapped Content Types table. The exact details of how metadata fields are moved between these mapped content types can be reviewed and edited by selecting the  icon to display the Target Metadata Mapping.

8.1.1. Reviewing default content type mappings

PMA has an automatic content type mapping feature but these should still be reviewed carefully because, even if a source content type is mapped, that doesn’t mean every attribute on that type is assigned to a target field.

8.2. Target Metadata Mapping

Target metadata mapping is the process of defining for each target content type, how its metadata fields are populated. In many cases a field may be populated with the relevant metadata field from the source item, but this feature provides the opportunity to alter the data during the migration if required.

Some customers take the opportunity to simplify their data and reduce the number of content types and/or content of fields during migrations.

A target content type may differ from the source content type in several ways:

- Number of metadata fields
- Valid field values
- Mandatory v Optional

PMA provides a rich set of capabilities to smoothly migrate metadata in such cases.

Select the appropriate Content Type mapping from the Mapped Content Types to configure mapping.



FIGURE 63 - MAPPED CONTENT TYPES LIST



Metadata mappings for File > Document

Define how the content of each target metadata field should be populated. [Learn more](#)

Target Metadata	Parameter Metadata	Parameter Type		
Name	Name	Metadata		
Title	Name	Metadata		
Created	Datecreated	Metadata		
Modified	Datemodified	Metadata		
Document Created By	GetMappedUser	Function		
Document Modified By	GetMappedUser	Function		
FileCheckinComment	—	—		
Compliance Tag	—	—		
Uri	—	—		

[← Back](#)

FIGURE 64 - CONFIGURING POPULATION OF TARGET METADATA

Metadata mapping configuration displays a table of target fields. For each field, the Mapping type displays the method used to populate the field (i.e. Metadata, Constant or Function) and the Source Metadata contain information on where the value comes from (either source field name, a constant/fixed value or name of function as applicable). Use  to add new mapping to a target metadata property or  to edit existing mapping.

For each Target Metadata field, there are 3 different methods which can be used to populate it.

- **Source Metadata** - The target field is populated using the value from a specified source metadata field.
- **Constant** - The target field is populated with a specified fixed value.
- **Function** - The target field is populated using the output of a function or PowerShell script. Both of which may use source properties or other values to help generate the value to populate the target field. For example, populate the target by prefixing a string to the content in source field 'RoomID'. For the full list of functions available See 14.1. Built-in Functions for details.

Term stores

The setting of term store fields is supported, if multiple values need to be assigned they should be separated using ;# e.g. Term store 1;# Term store 2.

Hidden SPO fields

When migrating to SPO by default, all fields are shown, irrespective of their hidden status.

To alter this so that hidden fields are not displayed in metadata mapping, alter the PCS configuration file, setting the configuration key to True and restarting the PCS client.

```
<add key="SharePoint.IsDiscoverHiddenMetaFields" value="True" />
```

8.2.1. Populating Target using Source Metadata

Selecting the Source metadata field will display list of source metadata field available. In this example below, the target metadata field Created is being populated by the DateCreated source metadata property.

Populating Target Metadata Field

Select the appropriate mapping type below to be used to populate target field.




FIGURE 65 - POPULATING TARGET USING SOURCE METADATA

Selecting the Source metadata field will display list of source metadata field available. In this example above, the target metadata field Created is being populated by the DateCreated source metadata property.

8.2.2. Populating Target using Constant value

Use this option to specify a Constant(fixed)value for a target metadata field.




FIGURE 66 - POPULATING TARGET USING FIXED/CONSTANT VALUE


8.2.3. Populating Target using Functions

A function can take in one or more parameters and use these to generate a resulting output which is used to populate a target metadata field. The function can either be a built-in function or a custom created function using PowerShell.

NOTE: Migration performance may be significantly impacted if using Powershell functions, especially if processing .CSV files due to the the time take to execute logic for each item. So script performance should be optimized where possible, especially for larger migrations.

Target metadata population using built-in functions

Choose the **Function** option and then the **Select** option



The screenshot shows a configuration interface for 'Target Metadata'. It has a header with 'Target Metadata' and 'Name (Name. -)'. Below this, there are three radio button options for 'Mapping Type':

- Metadata**: Use content of source field to populate target
- Constant**: Use constant value to populate
- Function**: Use Programming function to populate target (This option is selected and highlighted with a red box)

Below the 'Function' option, there is a text input field labeled 'Function *' and a blue 'Select' button (highlighted with a red box).

FIGURE 67 - POPULATING TARGET USING OUTPUT OF A BUILT-IN FUNCTION

A list of function areas is displayed broken down into the following categories.

Misc, StringFunctions, Math, Date & Time,Drupal8, OCR and CustomScripts

A full list of all the functions can be found here [14.1. Built-in Functions](#)

Expand the relevant category and select the function to use and then press the **Select Function** button.

Populating Target Metadata Field

Select the appropriate mapping type below to be used to populate target field. [Learn more](#)

Target Metadata: FileCheckinComment (FileCheckinComment, -)

Mapping Type:

Metadata

Use content of source field to populate target

Constant

Use constant value to populate

Function

Use Programming function to populate target

Function * Select

Specify details of parameters to be passed to selected function. For each parameter specify if a constant value or a source metadata field should be used.



Parameter Name	Parameter Type	Source
stringOne	Constant	
stringTwo	Constant	

FIGURE 68 - CONFIGURING PARAMETERS TO PASS TO FUNCTION

Once the function is selected, the next step is to configure how values are passed into that function. A table is displayed showing each input parameter that the function requires.

The **Parameter Type** defines how the parameter is populated. This can either be **Constant** or **Metadata**. The source column should either contain the value for the Constant or the source metadata field name.

Function * Select

Specify details of parameters to be passed to selected function. For each parameter specify if a constant value or a source metadata field should be used.

Parameter Name	Parameter Type	Source
stringOne	Constant	Migrated from FileShare
stringTwo	Metadata	Uri


FIGURE 69 - EXAMPLE OF PARAMETERS PASSED TO FUNCTION

In this example a target field is being populated using the Concat function to join a fixed string value and the URI source metadata field.

GetMappedUser Function

Target fields of type User or Group should be mapped using the function GetMappedUser(as they are by default). This ensures that these field types are populated correctly using the information with the security mapping table.

Editing Built-in functions

All the built-in functions can be edited using the  icon with the exception of those in the Misc Category.

NOTE: There is only once instance of these functions per server, so editing a function used by one job may have unintended consequences on other migration jobs.



Math			
SUM			
Round			
Absolute			
Power			

FIGURE 70 - SELECTING BUILT-IN FUNCTION TO EDIT

This will display details of the function including the parameters and the PowerShell that implements the function. Each parameter can be referred to in the script as it's parameter name. So for example, a parameter called JobTitle will be accessible in the code as \$JobTitle.

Add/Edit Function

Functions can be used to populate fields. [Learn more](#)

Name*
SUM

Group*
Math

Description
This function will return sum of THREE given numbers.

Parameters for this Function

Name	Type	
stringOne	String	
stringTwo	String	

Specify test values for parameters below to confirm function behavior is correct

Name	Test value
stringOne	
stringTwo	

Script

```
[Int]$stringOne+[Int]$stringTwo+[Int]$StringThree
```

Function Testing output

Test Function Cancel Save

FIGURE 71 - ENTERING TEST PARAMETERS TO TEST FUNCTIONS

The built-in SUM function normally adds two values. In the example above, we've altered it to add 3 numbers. The new parameter has been named 'StringThree' and is available in the script as a variable \$StringThree.


All the parameters will be listed in the Test Values section where test values can be manually specified. Use the **Test Function** option to execute the script using the value parameters specified to ensure it works as required.

8.2.4. Populating Target using PowerShell

As well as using built in functions it's possible to create your own functions. This feature is a powerful way to populate the contents of target metadata fields as it allows the output of a customer written PowerShell function to populate a specified metadata field. As with the built-in functions, a customer defined list of parameters can be specified.

Creating New Function

First, select the field to be populated with the function. On Content Type and Meta data mapping, select the for the Mapped Content Type to be altered.

In the table of target metadata fields, select  for the metadata field to be populated with PowerShell function.




FIGURE 72 - POPULATING TARGET USING A NEW FUNCTION

On Mapping Type screen, Choose **Function** and then the **Select** button

On the Programming Functions screen select **Create New Function**

Programming Functions

Function Library

Select an existing function or Create New Function to populate target metadata field. [Learn more](#) 

[Create New Function](#)

FIGURE 73 - CREATE NEW FUNCTION OPTION

New Function Definition

Add/Edit Function

Functions can be used to populate fields. [Learn more](#)

FIGURE 74 - DETAILS REQUIRED FOR NEW CUSTOM FUNCTION

Name: Name assigned for new function

Description: Description of function

Group: From the drop down, select **Custom Scripts**

Parameters for this function

Use the option to specify parameters that the function requires.

FIGURE 75 - DEFINING PARAMETERS FOR NEW FUNCTION

Use  to specify the name and datatype for each function parameter.





FIGURE 76 - ENTERING TEST VALUES FOR NEW FUNCTION

As parameters are specified, they will appear on the test parameters area. Use the  option to enter test values for these parameters to pass to the PowerShell script. Use the **Test Function** option to execute the script using the test parameters. The output of which will appear in the Output window.

Example PowerShell Function

```
$Age_bracket=Switch($Age)
{
  {$_ -le 10}           {"Very Young"}
  {$_ -gt 10 -and $_ -le 17} {"Young"}
  {$_ -ge 18 -and $_ -le 100} {"Adult"}
  {$_ -gt 100}         {"Very old!"}
}
return $Age_bracket + "-" + $surname
```

The PowerShell script will have access to the passed in parameters So \$Age and \$Surname are variables which are available for the example to use. It will use the \$Age parameter to determine an 'Age Bracket' and concatenate that with the Surname to return this as the return value of the function which is then used to populate the Target metadata field.

Working Example

Add/Edit Function

Functions can be used to populate fields. [Learn more](#)

Name*
MyFirstFunction

Description
Example Function

Group*
Custom Scripts

Parameters for this Function

Name	Type	
Age	Integer	
Surname	String	

Specify test values for parameters below to confirm function behavior is correct

Name	Test value
Age	35
Surname	Mahoney

Script

```

1 Sage_bracket=Switch($Age)
2 {
3   {$_ -le 10}           {"Very Young"}
4   {$_ -gt 10 -and $_ -le 17} {"Young"}
5   {$_ -ge 18 -and $_ -le 100} {"Adult"}
6   {$_ -gt 100} {"Very old!"}
7 }
8 return Sage_bracket + "-" + $surname

```

Function Testing output

Adult-Mahoney

Test Function

Cancel

Save

FIGURE 77 - EXAMPLE OF FULLY DEFINED CUSTOM FUNCTION

Use **Save** once the function is completed and then the next step is to configure how values are passed to the function. The table below will be displayed/

Use the Parameter Type field to specify whether the parameter should be populated with a constant value or a source metadata field. Use the to specify details.

Specify details of parameters to be passed to selected function. For each parameter specify if a constant value or a source metadata field should be used.

Parameter Name	Parameter Type	Source
Age	Constant	
Surname	Constant	

FIGURE 78 - CONFIGURING HOW PARAMETERS ARE PASSED TO CUSTOM FUNCTION

When using metadata type mapping, selecting the Source field will display a dropdown list of all the metadata fields for the relevant source content type.

8.2.5. Using Document ID Service

If the target SharePoint site has Document ID service feature enabled, then PMA will also allow you to map Document Id and Document ID URL fields during migration.

To add metadata mapping for Document ID and Document ID URL fields follow the steps given below:

- Open the content type mapping Settings.
- Select any document content type mapping.
- Select the Document ID Target metadata field and map it to equivalent unique source metadata field or if none exists, a custom PowerShell function could be written to auto generate a unique Document ID number.
- Document ID URL (Optional). By default, when a Shortcut Link is migrated, the URL of the item it points to will be the exact target path the referred to item was/will be migrated to. That means if the target item is later moved, the Shortcut will no longer work. If using the SharePoint Document ID service and, specifying this Document ID URL then this Document ID URL is populated into the Shortcut Link instead of the exact path. This then means that the Shortcut URL would still function even if the target item the Shortcut points to is moved.

A Custom Function can be used to generate unique Document Id URL for each document by adhering to below SharePoint Document ID URL format.

```
http://xxx.sharepoint.com/_layouts/15/DocIdRedir.aspx?ID=<DocID>,<DocID>
```

Where <DocID> is the name of the target metadata field storing the Document ID configured in steps above.

8.3. Custom Classification

Custom classification is a powerful feature to allow specific items to be assigned to a Target Content Type independent of what their source content type is. Customer defined criteria can be specified to identify such items. For example, a 'HR Items' custom classification can be defined as any source items that have 5 digit number in the Name metadata field. Just like normal content types, these custom classifications then need to be mapped to a suitable target content type.

Example #1:

Scenario: In a File system migration, most files should be migrated 'as is' but for those items located in a specific folder the filename will contain an employee ID and there is a requirement for this employee ID to be used to populate a target metadata field for these items.

Solution: In this case, Custom Classification 'HR Items' can be created and used to detect these specific items and mapped to the target content type 'HR Items'. Afterwards, using

the target metadata mapping feature for the 'HR Items' a target metadata field 'EmployeeID' can have a Function associated with it which would execute a customer written PowerShell script to process the filename source field parameter passed into it and parse it to return the employee ID which then populates the EmployeeID field.

In this way then, Custom Classification is being used to select the items which need to have their metadata properties processed in a different way to other items of the same source content type.

Example #2:

Documents and Images in ShareFile are saved as **Documents**, whereas **SharePoint Online** has a specific Content Type **Image**. Simply mapping items of Source content type **Documents** to **Image** target content type would mean images AND documents from ShareFile being migrated as Documents. Instead we need a way to identify these images that are currently classified as Documents in ShareFile and process their metadata properties differently.

As many Custom Classifications can be created as required.

8.3.1. Creating a Custom Classification

In the steps below, a new Custom Classification will be created called 'Custom Images' and is defined by items in the source with file extension of .jpg or .png. This will be named 'Custom Images' and can then be mapped to the SharePoint target content type 'Image'.

To Add/Edit a Custom Classification select **Migration Preparation Phase > Content Type & Metadata Mapping**.


Click  next to Custom Classifications to open **Add/Edit Custom Classification** page



FIGURE 79 - CREATING NEW CUSTOM CLASSIFICATION

Custom Classifications can be edited or deleted by clicking on   respectively.

The **Add/Edit Custom Classification** screen is displayed to define a new Custom Classification.

Add/Edit Custom Classification

Custom Classification allows scripts to be written to change existing Content Type for selected Items [Learn more](#)

Classification Name * Base Content Type *

Select Variable

List of Variables available to Script

Name
Name

Specify test values for parameters below to confirm function behavior

Name	Test value
Name	

Script

```

1 $result = $FALSE
2 if($MigrationItem.SI.ItemName)
3 {
4     $ result =
5     $MigrationItem.SI.ItemName.Contains(".png") -or
6     $MigrationItem.SI.ItemName.Contains(".jpeg") -or
7     $MigrationItem.SI.ItemName.Contains(".jpg") -or
8     $MigrationItem.SI.ItemName.Contains(".tiff") -or
9     $MigrationItem.SI.ItemName.Contains(".bmp")
10
11 }
12 $result
    
```

Function Testing output

FIGURE 80 - EXAMPLE CUSTOM CLASSIFICATION

Classification Name: This is the name for this custom classification.

Base Content Type: When creating a classification, select an existing content type to use as a template for source metadata fields that will be available for mapping to target.

List of Variable available for Scripting: The variables listed will contain relevant source metadata properties based upon the selected base content type and can be used by the script. Each will then be available as their name in the script, so Title attribute is stored in \$Title variable for example.

Specify test values: When developing the script, use this to specify test parameter values to confirm the PowerShell is working as expected.

Script: This is where the PowerShell script should be written. The script should evaluate the parameters passed to it and should return \$true if the item should be assigned the associated custom content type, otherwise return \$false.

Click **Evaluate** to run the PowerShell using the test values provided.

The output of the script will appear in the Function Testing output window.

Once testing is complete, use Save option to create the new custom classification.

The **Add/Edit Custom Classification** script should evaluate to **True** for custom classification to work properly. Anything that evaluates to **False** will skip the added Source classification settings.

Following the steps above, the Custom classification 'Custom Image' is then available to map to an appropriate Target Content Type (e.g. Image)

Note: It's essential to review the metadata mapping once the custom classification is mapped to a target content type.

Note: Custom classifications will only get executed if they have been mapped to a target content type.

Custom Classification Execution

The actual execution of these classification scripts will occur when running the Step 2 – Classify in the Migration Phrase. For each item, each of the script(s) will be executed till one returns a value of 'True'. So for example if there are 3 Custom Classifications, then Step 2 Classify - Assign Target Content Type will run each script, passing to it the relevant item metadata values till one of the scripts returns 'True' or all scripts have been executed for the item. If none of the scripts return 'True' then the original Source Content Type is assigned to the item.

Note: The order in which the classification scripts are executed against each item is random. That means it's essential that these scripts do not 'overlap' one another i.e. two scripts could potentially return 'True' for the same item. When developing a script to identify an item if there are other custom classifications, it may be necessary to update those scripts to ensure that they will exclude such items.

8.3.2. Custom Classification Scripting Objects

The following objects can be used in the PowerShell script to classify items.

- **MigrationItem**
 - **SI** - The source representation of the item
 - **ItemName** - The name of the item as shown in the user interface.
 - **MimeType** - The file extension of the item.
 - **Uri** - The logical path of the item.
 - **AlternateUri** - The path to the binary if the item is a file.
 - **GroupId** - The document identifier that is common across all document versions.
 - **VersionLabel** - The major version.
 - **SubVersionLabel** - The minor version.
 - **EntityCategory** - 0 for containers, 1 for files and links.
 - **EntityType** - File, Link or Folder.
 - **ContentType** - The content type classification of the item.
 - **ItemSize** - The size of the content (in bytes).
 - **Level** - The depth of the item in the folder tree.
 - **HasUniqueSecurity** - Whether the item has security, information assigned.

- **SIC** - The source metadata exposed as an XML string.
- **Log** - A logging object of type log4Net.ILog - this can be used to write messages to the application log with statement such as `$Log.DebugFormat("Doing x for item with path {0}", $MigrationItem.SI.Uri);`

Example Classification Scripts

Description	Example Script
Classifies Media files based upon Video or Audio content type	<pre> \$result = \$FALSE If (\$migrationItem.SI.ItemName) { \$result = \$MigrationItem.SI.ContentType -eq 'Video' -or \$MigrationItem.SI.ContentType -eq 'Audio' } \$result </pre>
Classifies Image items based upon file extensions (png,jpeg,jpg,tiff or bmp)	<pre> \$result = \$FALSE If (\$MigrationItem.SI.ItemName) { \$result = \$MigrationItem.SI.ItemName.Contains(".png") -or \$MigrationItem.SI.ItemName.Contains(".jpeg") -or \$MigrationItem.SI.ItemName.Contains(".jpg") -or \$MigrationItem.SI.ItemName.Contains(".tiff") -or \$MigrationItem.SI.ItemName.Contains(".bmp") } \$result </pre>
Classifies items based upon size and example of using Logging.	<pre> \$result = \$FALSE if (\$MigrationItem.SI.ItemName) { if (\$MigrationItem.SI.ContentType -eq 'File') { if (\$MigrationItem.SI.ItemSize -gt 1048576) { \$Log.DebugFormat("Large Item sized {1} for item {0}", \$MigrationItem.SI.Uri,\$MigrationItem.SI.ItemSize) \$result = \$true } Else { \$Log.DebugFormat("Small Item sized {1} for item {0}", \$MigrationItem.SI.Uri,\$MigrationItem.SI.ItemSize) } } } </pre>

	<pre>} \$result</pre>
Classifies all files to a single content type	<pre>If (\$MigrationItem.SI.EntityCategory -eq 1) { return \$true; } else { return \$false; }</pre>

9. SECURITY MAPPING

Items in a source will have some kind of user or permission information associated with them and the security mapping feature can be used to help transfer this information into the target if necessary. For example, the Created By of a document in the source may be a name of a user but in the target, this needs to be in an email address format.

Security Mapping uses a table of source values which is edited to associate these entries with a new target value. This is typically achieved by editing a .CSV file which can be exported and imported into the client.

Security mapping is required because such information stored on the source may not be directly transferred 'as is' because it may not be compatible with the requirements of the target platform. For example a document author may be a simple text string in the source but must be an email address in the target.

9.1. Security Entities: User, Group, Permissions

User and Group mapping is mandatory step, it allows the conversion of User and Group data to something suitable in the target system so that if User "ShelleyP" or Group 'Senior Leadership' appears on the source item then replace this with a suitable user or group as specified in the mapping e.g. Percy.Shelley@acme.com. The result of the mapping will affect the CreatedBy/ModifiedBy fields in the target. Any user or groups not mapped will cause the relevant items to fail migration unless the 'Default' feature is used, see below for more details.

Permission mapping is an optional step. It's the process of mapping a type of access right on the source to a suitable access right on the target. For example, a user may have read access on a folder in the source and this needs to be mapped to the equivalent Read access in the target. This information is used with the user/group mapping so that User "ShelleyP" who has "Read" access on the source is represented as Percy.Shelley@acme.com with "Read" access for the migrated item.

NOTE: If no permission mapping is specified then no specific permissions are applied to migrated items, and so they would inherit their access permissions from the target.

For each of the entities, there is the option to download the relevant data to .CSV file were it should then be modified (preferably in Excel) to add mapping information and then the updated file can be imported back into PMA.

NOTE: Permission mapping capabilities are limited when migrating to M-Files or File System. Contact technical support for more information.

9.2. Configuring User Security Mapping

Example: Download a User template, modify the CSV file to add user mappings and import the modified file.

Select **Migration Preparation Phase > Security Information Mapping** and then on the **User** card, select the Download Template icon. The .CSV file will be populated with user information that may need to be mapped to a suitable target.

Use Mapping files to map security information between source and target. Download the appropriate template for the type of data you want to map and then use Import Mapping option. Learn more [↗](#)

Security Information Type

User

User mapping allows you to map individual users that have been granted access on the source system to a suitable account or group that exists on the target system

↓ 📄 👤 🗑️

Group

Group mapping allows you to map groups that have been granted access on the source system to suitable group or user that exists on the target system

↓ 📄 🗑️

Permission

Permission mapping allows you to specify how to map a specific type of access on the source system into a suitable access permission on the target

↓ 📄 🗑️

FIGURE 81 - DOWNLOADING USER SECURITY INFORMATION

	A	B	C	D	E
1	Mapping_Type	Source_Type	Source_Value	Target_Type	Target_Value
2	user	user	Mike Bilsborough	user	mike.bilsborough@newcorp.com
3	user	user	Mike.bilsborough@contoso.com	user	mike.bilsborough@newcorp.com
4					

FIGURE 82 - COMPLETED USER MAPPING EXAMPLE

Edit the .CSV file to add a Target type and Target value that exists in the Target. Only the Target_Type and Target_Value columns need to be edited.

Target_Type - Defines whether the entry should be mapped to a **User** or **Group** in the target. If a user UPN is external then external sharing needs to be enabled on the tenancy. Target_Type should only be Group if using SharePoint Groups.

Target_Value - UPN for the respective user or group.

NOTE: A user may appear in two rows, as both a “Display Name” and an email address as shown in the example above and both of these need to be assigned target values.

NOTE: The .CSV file is populated using values from the CreatedBy and ModifiedBy fields in the source. So additional entries may be required.

Once completed, the modified file should be imported by selecting Import icon on the User card and select the updated security mapping file.

The process for modifying Groups and Permissions is the same as for Users.

Target Content Types may contain User or Group type fields which may need to be populated during migration. The information in these mapping tables will be used to map source values to new target values for these fields using the GetMappedUser function.

Note: If an entry has no target information or the target value specified does not exist then the relevant items will fail migration. Security Mapping 'Catch All'

After import, use the Validate User details option to check the target details are correct and review them using the Download Verified Security Mapping option.

In some scenarios, e.g. if a user has left the company, it makes no sense to map security entries for these users and often these users are not in the target system at all. However, the target platform may still require some user information to allow the items to be created and thus migrated.

Within the security mapping file a 'Default' value can be specified which is used for any user that does not appear at all in the User Mapping table.

Example *Default User Mappings Entry*

Mapping_Type	Source_Type	Source_Value	Target_Type	Target_Value
User	User	Default	User	orphanusers@acme.com

In the above case, any users with no entries in the mapping file will be assigned the specified target value. If a user entry is added but target information is blank or does not exist, the items will fail migration. So, it's important users without a value target entry are removed from the mapping table.

If no default entry is specified, then any items without an unmapped user or group will fail with an error similar to: -

Error: Failed: Get Mapped User: Did not find Mapping for User : [acme\shelleyp]

If a user or group is mapped to a target that does not exist the migration will fail with an error similar to: -

Error: SharePoint Error: The specified user percey.shelley@acme.com could not be found

Default entries can be applied both to user and to groups.

9.2.1. Processing empty source user fields


In some cases, the User field in the source system may be blank, in that case a User entry for PVQ_BLANK will be listed in the downloaded user mapping file. The target value for this should be the UPN for an account to be used when the source user field is empty.

If an entry with a target value of PVQ_SKIP is created then the value specified in the **Default User** field on the relevant source connection will be used for empty User fields.

Mapping_Type	Source_Type	Source_Value	Target_Type	Target_Value
User	User	Use Default User Value	User	PVQ_SKIP

9.2.2. Verifying User Mappings

The target address specified for users in security can be validated before actual migration using the Verify option.



Selecting this option with check each target address to ensure it is valid and report any errors.

After the check is complete, select the “Download verified security mappings” option. This will generate a report which is in the same format as the user mapping report that was imported but includes a new ‘VerificationResult’ column with the status of the verification of the target, (either “User found”, “User not found” or “Target not specified”). Review the report and if any entries have the “User not found” or “Target not specified” status then correct these in the mapping file or target system as appropriate, delete the existing mapping and import and verify again.

9.2.3. Sample Security Mappings

Example User Mappings

Mapping_Type	Source_Type	Source_Value	Target_Type	Target_Value
User	User	EVAdmin	User	evadmin@acme.com
User	User	Percy Shelley	User	percy.shelley@acme.com
User	User	Nevil Hanson	User	n.hanson@acme.com

FIGURE 83 - EXAMPLE OF USER SECURITY MAPPING

Example Group Mappings

Mapping_Type	Source_Type	Source_Value	Target_Type	Target_Value
Group	Group	Senior Leadership	Group	slt@acme.com
Group	Group	Security Team	Group	Security@acme.com
Group	Group	Data Protection Team	Group	dp@acme.com

FIGURE 84 - EXAMPLE OF GROUP SECURITY MAPPING

Permission Mapping

NOTE: If there is no requirement to migrate container or item level security but to migrate only CreatedBy and ModifiedBy fields, then permission mapping is **not** required.

Example Permission Mappings

Mapping_Type	Source_Type	Source_Value	Target_Type	Target_Value
Permission	AccessRights	FullControl:AccessPermit	PermissionLevel	Full Control
Permission	AccessRights	Delete:AccessPermit	PermissionLevel	View Only
Permission	AccessRights	Read:AccessPermit	PermissionLevel	Read
Permission	AccessRights	Write:AccessPermit	PermissionLevel	Edit

For Mapping type permission, Mapping_Type, Source_Type and Target_Type are always the same as above, it's only the mappings in Source_Value and Target_Value that will need to be changed.

The target values should contain the permission role. E.g. Contribute, Full Control or whatever additional roles the site administrator may have created.


Samples files can be found installation folder which is by default, C:\Program Files\Proventeq\Proventeq Content Suite\SampleFiles.

10. PHASE 2 – GENERAL SETTINGS

General Settings contains settings controlling behaviour of migration jobs. Such as how to manage Embedded Links, handline characters that are valid in the Source but invalid in the Target etc.

Job Name

Embedded Links

Update Embedded Links 

For link resolution, its essential to run migration to Create Item Manifest (Step 3) for all items first, before migrating data to target (Step 4).

Migrate Items with Broken Embedded Links

Only migrate Resolvable Links

Office Document (97 - 2003)

Word Excel PowerPoint

Office Document (2003 Onwards)

Word Excel PowerPoint

Other Documents

PDF Rich Text Document

FIGURE 85 - GENERAL SETTINGS

NOTE: Above is a subset of all settings. Prior to the migration processing you should review all of the settings available to ensure they are correct.

Job Name: This was set during the initial job creation and can be changed here.

Update Embedded Links can be used to re-establish hyperlinks in well-known Source file contents with the new location of linked files in Target container while performing the migration. This feature is not mandatory for migrating content from Source to Target.

NOTE: Enabling this feature will make the migration significantly slower and requires Microsoft Office to be installed on the PMA server.

NOTE: When using this feature, it's essential to take a two pass approach to the migration. When in the migration phase, first execute **up to Step 3-Transform ONLY**. This will generate the necessary information about the location items will be migrated to. After this has been executed for **all items**, then Step 4 – Load can be executed and in doing so, this feature will replace the links within document types specified above with the new target information generated during step 3. The reason why Step 3 must be performed is to ensure that the target URL for all embedded items is known, before any migration which may refer to them takes place

The document types supported are :-

File Type	Extensions
Word	.doc .docx
PowerPoint	.ppt .pptx
Excel	.xls .xlsx
Other	.pdf .rtf

NOTE: Embedded links in encrypted/password protected items cannot be processed

Migrate items with Broken Embedded Links

A document may contain a link to another item where the target URL is not/cannot be determined. For example, referring to another document that has been deleted in the source or potentially not captured during the Discovery process. Such links are termed Broken Links. This setting controls whether items should be migrated even if it refers to an item where the Embedded link will no longer function in the target. The default behavior is that such items would not be migrated.

Invalid Characters

Replace Invalid Characters: Targets often have different character limitations than the source so it may be necessary to replace such characters during migration to ensure the item is successfully migrated. The Pre-Check feature will identify items containing invalid characters.

The default list of invalid characters is suitable for migrations to SharePoint Online.

Invalid Characters

Replace Invalid Characters: " + * : < ? > / \ | \t \n \b \r\n with: *

FIGURE 86 - CONFIGURING INVALID CHARACTER REPLACEMENT

Replace with allows you to specify the character to replace any of the invalid characters specified. You can specify no replacement character, if required in which case the character(s) are removed.

Example An invalid filename like **Help ? information.txt** becomes **Help _ information.txt**

File Handling

File Handling

Migrate Duplicate Files (will append a unique number)

FIGURE 87 - CONFIGURING FILE HANDLING SETTINGS

Migrate Duplicate Files: If selected (default) then if an item with the same exists in the migration job, then during migration, a unique document name will be created by appending an auto incrementing number as a file name suffix. If unselected, any duplicate items will not be migrated.

For example, 3 files with same name as Proventeq User Guide.pdf migrated to the same folder will be migrated with names of

- Proventeq User Guide.pdf
- Proventeq User Guide (1).pdf
- Proventeq User Guide (2).pdf

Advanced General Settings

Advanced

Discovery

WARNING: Discovery Filter can now be edited. Please read section "Editing Discovery Filter" in the User Guide to ensure correct usage of this feature.

Load

WARNING: Load is enabled regardless of any load restrictions. Please read section "Advanced General Settings" in the User Guide to ensure correct usage of this feature.

Discovery

By default, after a discovery has begun, it's not possible to edit the discovery filter. This is because doing so could create inconsistent results. For example having no filter and then adding a filter after initial discovery does not remove existing discovered items. In some scenarios it can be useful to edit the filter, for example to correct a wrong filter value. By selecting this option, it allows the Discovery filter to be edited even after discovery has started.

Load

By default, the processing stage 'Step 4 – Migrate to Target' cannot be selected in the Processing Screen if the "Update Embedded Links" option has been selected and not ALL items have been first processed up to the 'Step 3 – Transform – Create Item Manifest' step. Selecting this option allows the 'Step 4' option to become available even if all items have not been transformed. Note the consequences of selecting this option means that items will be migrated but may contain embedded links which have not been updated (because transform has not occurred for all items) and so will not point to the new location of migrated items.

11. PHASE 3 – MIGRATION PHASE

The migration phase deals with the final preparation and migration of items into the target. It consists of a set of 4 steps that are executed for each item, in doing so evaluating the settings specified in phase 2 i.e. structure mapping, content type and security information.

Each step will output data and during the pilot stage it's recommended to run each step separately for a subset of data to review the output in the Items List before then executing the next step for the items.

Executing a step will also execute any previous steps (if it hasn't previously been executed), so executing step 3 for example also executes step 1 and step 2 first.

11.1. Migration Steps

Select the **Migration** option on the **Migration Dashboard** to display the migration steps.

3. Migration Phase [Learn more](#)




FIGURE 88 - STARTING DATA MIGRATION

Data Processing and Migration

There are several steps to migration of data. You can review the result using the Items List to verify if they are executed correctly. [Learn more](#)

Use the slider to select the step up to which all items should be processed

Use Items List option to review results




FIGURE 89 - LIST OF STEPS IN DATA MIGRATION

Migration is actually a set of 4 sequential steps that need to be executed for each item. Using the slider control you can select how many steps to execute. This allows you to review the output of that step for the processed items, before continuing.

The output generated from a step remains with that item and is not re-generated even if that step is executed again. This means if step 2 (Classify) has assigned content type or step 3 (Transform) has built the Item Manifest they will remain with that item, even if subsequent changes elsewhere have been made to migration settings (e.g. Structure mapping, content and security mappings). It also means metadata captured in Step 1 is unchanged, even if such data is altered in the source system.

If steps 1 to 3 are run and the resulting output is not correct, then use 'Undo' option to delete this data. The 'Undo' option is only available once any step has been executed.

Use the **Item Details** screen to display the details of items in the **Items List** to view the output from these steps.

Step	Verification
1	Items list shows source metadata content. Ensure this is complete and correct.
2	On the Item details review the Source Content type
3	On item details, review target metadata properties. Target URL etc.
4	Review item in target location, content, metadata properties, access permissions if relevant.

To start processing, select the step by using the slider or clicking on the card and then select the **Start Process** option.

Migration Run Settings

- **Include previously failed Items Option**
If selected, items that previously failed will be resubmitted for processing along with any items still awaiting migration.
- **Maximum number of items**
Select number of items to be processed.
- **Maximum number of threads.**
Defines how many items are processed concurrently. The optimal value for this setting depends on various factors including the number of documents going into each site collection. A higher number of threads gives better performance when you have fewer site collections with lots of documents in folders.

NOTE Processing can take several hours or more, depending on the amount of data and selected processing step.

11.2. Problem Item Processing

11.2.1. Empty Files

This allows control over the migration processing of source items that are empty (0 byte). There are three options:-

- **Do not migrate, mark as failed** – This will not attempt to migrate the item, instead immediately marking it as ‘failed’.
- **Migrate item as is** – (default) This will attempt to migrate the item. Depending upon whether the item is a version of an item, the target system may allow the item to be migrated successfully.
- **Replace empty content with placeholder text** – This option allows the content of these 0 byte items to be replaced with placeholder content based upon its type so Word, Excel, PPT and text. You’ll find existing template placeholder files in C:\Proventeq\Placeholders\default. When a 0 byte item needs to be migrated its content will be replaced with the placeholder content based upon the relevant file type so an empty Word document is replaced by a Word document containing placeholder content and so on. Using this feature allows all source to be migrated regardless of content size.

NOTE: These placeholder files can be edited if required. We recommend that if edits are made to these placeholder files that they are saved into C:\Proventeq\Placeholders\override and PMA will process these in preference to the default location. Otherwise, any changes to placeholders in the default location may be lost if the PMA software is upgraded as the installation would overwrite these existing files.

11.3. Transform Warning

If the option 'Update Embedded Links' is selected in General Settings then this warning message below may be displayed at the top of the processing screen and the option "Step 4 – Migrate to Target" cannot be selected. This is because for embedded link updates to be successful, the target URL for ALL items must first be determined by running up to Step 3- Transform for all items first, so that then as items are migrated these embedded links in the content can be updated to contain the new URL for these linked to items (even if at this stage these links refer to items that may not have been migrated yet).

Data Processing and Migration

There are several steps to migration of data. You can review the result using the Items List to verify if they are executed correctly. [Learn more](#) 

 Currently 0% of items have been transformed. 100% items should be transformed to Update Embedded Links.

Running Step 3 – Transform may not be successful for all items. If after investigation, it's confirmed that it's not possible for all items to be successfully Transformed then select the 'Load' option in the Advanced section within General Settings as this will allow the 'Step 4 – Migrate to Target' option to be selectable. Using this Load option obviously means that any embedded links to these items that have failed to be transformed will not be updated and therefore the documents will keep their existing legacy links which will not function once source system is unavailable.

Advanced

Discovery

Load


WARNING: Load is enabled regardless of any load restrictions. Please read section "Advanced General Settings" in the User Guide to ensure correct usage of this feature.

11.4. Step 1 Extract – Extract metadata

The Discovery process will extract a standard set of properties from items in the source and record this information in the PMA SQL database which can then be viewed on the Item details screen accessible from the Items List

This step will retrieve further information, often specific to the source platform and once this data is extracted it can be used by subsequent processing steps. It's important to review these properties on the Item Details screen to ensure they are correct and complete.

Item Name: sqllexport.csv

Last Processed Stage	Processing - Capture Metadata
Status	
Status Message	Item processed successfully upto stage CaptureMetadata.
Id	268045
Group ID	3CB3029BC08D4DC74D68B2B22804D829
Extension	.csv
Last Processing Date	4/12/2022, 9:01:47 AM
Size	636 Bytes

Source Item

Item Name	sqllexport.csv
Content Type	File
Uri	C:\Users\Administrator\Documents\sqllexport.csv
Content Type Id	
Item Id	334008
Content Item Id	3CB3029BC08D4DC74D68B2B22804D829
Parent Name	Documents
Parent Item Id	334001

Captured metadata

Name	sqllexport.csv
Title	sqllexport.csv
Fullname	C:\Users\Administrator\Documents\sqllexport.csv
File extension	.csv
Date created	22/12/2021 6:26:12 PM
Date modified	22/12/2021 6:26:12 PM
Owner	BUILTIN\Administrators

FIGURE 90 - VIEWING SOURCE METADATA RETRIEVED BY MIGRATION STEP 1

In Items List the status will be 'Capture Metadata'

11.5. Step 2 Classify - Assign Target Content Type

The Content Type can be viewed in the Content Type field in the Source Item section of item details. This step will update the source content type of the item by execute any custom classification scripts, so running a migration to this step is unnecessary unless that feature is used. In Items List the status will be 'Classify'.

See Custom Classification [\[1\]](#) for further details.

Based upon knowing the source content type you can determine what the Target Content Type will be by viewing content type mapping.

As a reminder, content types define how properties are moved between the source and target items so it's critical that the correct Target Content Type is assigned based upon business requirements.

11.6. Step 3 Transform - Create Item Manifest

The Item manifest is a package of data that contains all necessary metadata associated with the item to be migrated. The manifest content is migrated along with the item content in Step 4.

This step populates the Item Manifest for each item by:

- Creating target metadata by using the assigned Target Content Type to apply appropriate metadata processing to the source fields.
- Creates structure mapping metadata by evaluating structure mapping to determine target location to migrate the item to.
- Creates security information metadata by evaluating security mapping.

In Items List the status will be 'Transform'.

NOTE: If the option to 'Update Embedded Links' is enabled in General Settings, it is essential that **ALL ITEMS** are **first processed ONLY to Step 3-Transform**. This is because this step determines the target locations of items which is then used in step 4 (Migrate to target) to replace existing embedded links with links to the new location items will be in once actually migrated. See 11.3. Transform Warning

11.7. Step 4 Load – Migrate to Target

This is the default step and will execute the following: -

- Retrieve item contents from the source and combine that with Item Manifest for that item.
- Based upon package size settings, a set of these items will be placed into a package and a request sent to upload then to Azure Blob Storage.
- Send notification to SharePoint to request that package is ingested.
- SharePoint will process notification and ingest item packages into target.
- Client will display progress,



FIGURE 91 - MIGRATION PROGRESS SCREEN

Packaging is the terms used for a technique used by PMA to improve migration performance into SharePoint. During migration, items are grouped together into packages and these packages are then uploaded into Azure. SharePoint will then process these packages asynchronous. Package verification is a process that PMA executes from time to time during migration to check the current status of any uploaded packages.

11.8. Migration Considerations

Loading data into the target is often the area where problems occur because it's ultimately a verification that the previous steps were correct. In some cases, failure may mean that an error occurred when attempting to migrate the item, in other situations an item may migrate to the target successfully but there are issues with the item.

'Failure examples'

- Item is migrated to the wrong location due to Structure mapping
- Item may incomplete or incorrect in the target due to content type/metadata mapping issues
- Incorrect target users or groups specified in security mappings

Since Load is the stage where content is retrieved and copied into the target, it's obviously an area where performance issues can arise.

For information on SharePoint best practices see <https://docs.microsoft.com/en-us/sharepointmigration/sharepoint-online-and-onedrive-migration-speed>

11.9. Undo Migration

The Undo option will reset the system back to the state it was after discovery by deleting any of the data generated from migration steps 1 – 4, including deletion of the items from the target. This means all the records captured by discovery are still in the PMA database and a re-run of Discovery is not required.

Note: Undo will 'reset' the license consumption for items undo is for steps 1-3 ONLY. Undo of migrated items does NOT reset the license. That means if an item is migrated to the target, then deleted and then re-migrated that would consume the license twice.

Undo can be used when a problem has occurred and so some of the steps that have already been executed need to be corrected and run again.

The undo option is displayed on the Data Processing and Migration screen once any of the steps in phase 3 (Extract, Classify, Transform or Load) are executed. If data has been migrated to the target undo option will delete them irrespective of whether they have been subsequently modified. The deletion may fail if retention plans do not allow items to be deleted.

Undo Scenarios

- Items are migrated to the incorrect location, due to structure mapping issues
- Migration items have incorrect metadata properties or content types
- Migrated items have incorrect security information
- Step 2 (Classify) or Step 3 (Transform) have been run but the results as shown in the Items List suggest the data is incorrect.
- Source item metadata has changed

Undo Migrated Data or Settings

This screen will help you to undo migrated data or settings. [Learn more](#)

The undo option will return the status of the migration back to the point where discovery is complete. All output from Phase 3 will be deleted. This means any migrated items will be deleted from the target, as well as any output generated from Extract, Classify and Transform steps. Security mapping information will remain.

Also undo any structure mappings

Start Process

FIGURE 92 - UNDOING A MIGRATION

If the “**undo any structure mappings**” option is selected, Undo will delete any structure mapping information. Content Type settings Security mappings are not removed by Undo.

11.10. Resolving migration errors

Errors are mostly like to occur when executing the Transform or Load stages.

To view failed items, use **Reports->Failed Items Report**

The **Status Message** column will may contain a numeric error code to identify the type of issue.

e.g.

046 Transform Failure - Error: Failed: Get Mapped User: Did not find Mapping for User: [Domain\Username]

Clicking on the error will access the online knowledge base and display a relevant article to help you understand and resolve the error.

11.11. Shortcut Links Migration

Shortcuts are standalone items in the Source which when opened will open the item they refer to. Using this option will migrate shortcuts to the target but will ensure that the shortcut is updated to refer to the new target location. The maximum processing speed of Shortcut Link migration is around 2000-3000 per hour so this should be factored into any migration planning.

The Discovery Statistics panel on the Migration Dashboard displays the number of shortcuts found in the source. To migrate shortcuts the 'Links' content type must be assigned to a target content type.

Note: Microsoft do not recommend the use of shortcuts in SharePoint.

Shortcut Migration - Migration job: File System Migration

This will migrate Shortcuts to the target [Learn more](#)




FIGURE 93 - STARTING SHORTCUT LINKS MIGRATION

11.12. Verify and communicate with end users

Ensure that the data has been migrated as expected using the mapping and security settings that have been configured. This is best done by logging into the Source and Target and ensuring the Folders and Files have been migrated and can be accessed.

Review the Source Data and the Target Data

- Using the structure mapping to confirm data has been moved to the intended location
- For each content type, review item and meta data is correct and that the items operate as expected in the target.
- Where different permissions mappings have been carried out, verify they achieve desired outcome

12. POWER BI REPORTS

Power BI Reports can be used to access the information in the Proventeq Migration Accelerator database to provide intuitive and interactive drill down reports. The reports can be viewing by using the Visualize option on the migrated dashboard after Pre-Checks option has been run.

Two warnings displayed when opening Power BI : -

1. Potential security risk

Displays warning about 'Potential security risk' due to the file using multiple data source. Click **OK** to continue.

2. Native Database Query

Displays warning to approve running native query. Click **Run**

12.1. General Distribution of Content

This report shows the general distribution of content within the system. This includes content type distribution, mime type distribution, version documents and documents under folders.

FIGURE 94 - POWER BI - GENERAL CONTENT DISTRIBUTION




FIGURE 95 - ANALYTICS – CONTENT SUMMARY

To navigate different reports using Navigation, please use CTRL+CLICK on the menu button on the left Menu panel.

12.2. Pre-Migration Checks- Version Continuity

Power BI Version Continuity Reports shows the items which are qualified in different categories where Proventeq will apply certain rule and configuration to resolve these target constraints.

FIGURE 96 - POWER BI – PRE-MIGRATION CHECK – VERSION CONTINUITY




FIGURE 97 - ANALYTICS – VERSION CONTINUITY

12.3. Pre-Migration Checks- Paths and Names

Power BI Paths and Names Reports shows the items which are qualified in different categories where Proventeq will apply certain rule and configuration to resolve these target constraints.

FIGURE 98 - POWER BI – PATHS AND NAMES




FIGURE 99 - ANALYTICS – PATHS AND NAMES

12.4. Pre-Migration Check – Folders & Files

Power BI Files Reports shows the results of several checks for folders and folders.

FIGURE 100 - POWER BI – PRE-MIGRATION CHECK – FILES




FIGURE 101 - ANALYTICS – FILES

Note: This report will highlight Max Size files, as Migration Accelerator supports migration of files up to 2GB

12.5. General Usage of Content

Power BI usage report shows the history of documents such as- when it has been created, modified, created date range, modified date range, created by, and modified by users.




FIGURE 102 - ANALYTICS – CONTENT USAGE

12.6. Container Analysis

Power BI Container report shows the hierarchy of the Source system.

FIGURE 103 - POWER BI – CONTAINER




FIGURE 104 - ANALYTICS – CONTAINER ANALYSIS

As container analysis is an intensive and complex operation, it is disabled by default. To enable, change the application configuration setting below to True and rerun discovery.

<add key="PerformContainerAnalysis" value="false" />

13. APPENDIX

13.1. Licensing

Each PMA server will require an activated license file to allow the product to operate. A license can either be activated online (presuming there is an internet connection) or offline where an activation request file can be generated and once emailed and processed by Proventeq, an activation response file can be upload to complete the license activation.

A License can support several migration paths e.g. ShareFile and File Shares to SharePoint Online.

License consumption is based upon the volume of data, so customers may purchase a 200GB license etc. An item will consume license as soon as any Migration Phase operations, such as Extract metadata, Classify etc. So even if no migration into the target has taken place, license will still be consumed. Discovery does not consume license.

NOTE: If the migration requires more than one PMA server then it's essential to understand the volume of data each server is going to migrate as license volumes are controlled on a per server basis. Incorrect amounts could lead to project delays due to license being fully consumed.

Delta migrations will consume license.

If the Undo operation is used, undo will free up license consumption for items processed up to steps 1-3 but NOT for migrated items. That means the undo of migrated items will effectively consume license twice.

PMA has a trial license and this is not based upon volume but the number of items discovered or migrated.

13.2. Discovery Filters

Note: CSV based filters are only supported when running in non SaaS mode.

13.2.1. Discovery Filter for ShareFile

A filter can be applied to the Discovery. Using a filter can speed up the Discovery process, as well as reduce the size of the databases created by discovery and ensures that the database doesn't contain any items which do not have to be migrated.

Filters allow a list of folder locations to be specified in a CSV file, so only these folders (and their child) will be captured in the discovery process. Anything not discovered will not be processed for migration.

Discovery Filter Syntax:

```
["ObjectType":"CSV","Filter":"<FilePath>"]
```

<FilePath> - File path of the CSV containing hierarchy path and app URI. It is mandatory to provide double backward slash ‘\’ in the file path.

E.g.

```
["ObjectType":"CSV","Filter":"F:\\Proventeq\\Configuration\\Product\\ShareFile\\Discovery Filter.csv"]
```

Example Discovery Filter for ShareFile

FIGURE 105 - SAMPLE CSV FILE

HierarchyPath	ApiUri
Virtual Root/Shared Folders/General Share/Test Data with Many Items/Folder 03/Folder 02/Folder 01	https://mycompanydemouser.sf-api.com/sf/v3/items{f06a707a-6562-47a5-a4ee-c73dce9f890f}
Virtual Root/Shared Folders/General Share/Test Data with Many Items/Folder 03/Folder 02/Folder 02	https://mycompanydemouser.sf-api.com/sf/v3/items{f04f4a49-31f2-44ec-be48-de526e8c6aa}
Virtual Root/Shared Folders/General Share/Test Data with Many Items/Folder 01/Folder 01/Folder 02	https://mycompanydemouser.sf-api.com/sf/v3/items{f054e657-e647-4647-b491-94cd09f02bfa}

The AppURI can be found on the details screen on the selected folder in ShareFile administration portal.

13.2.2. Discovery Filter for FileShare

A filter can be applied to the Discovery. Using a filter can speed up the discovery process, as well as reduce the size of the databases created by discovery and ensures that the database doesn't contain any items which do not have to be migrated. Anything not discovered will not be processed for migration.

It possible to limit the discovery using a filter.

- Capture only information in folders specified in a specified .CSV file
- Capture items CREATED before specified date
- Capture items CREATED after specified date
- Items of specified file extensions
- All items, except those of a specified file extension

Syntax:

```
["FilterType":"<FilterType>","ObjectType":"<File or Folder>","Filter":"<Filter>"]
```

Supported Filter Types

FilterType	Description	Object Type Supported
CSVInclude	Will discover folders provided in the CSV	Folder
DateBefore	Will discover files before the given date	File
DateAfter	Will discover files after the given date	File
ExtensionInclude	Will discover files which includes the given extension in CSV	File

ExtensionExclude	Will discover files which excludes the given extension in CSV	File
------------------	---	------

<ObjectType> - Folder or File depending upon FilterType.

<Filter> -

Example Limiting File Share discovery using CSVInclude

- [{"FilterType":"CSVInclude","ObjectType":"Folder","Filter":"F:\\Proventeq\\Configuration\\Product\\ShareFile\\Discovery Filter.csv"}]

Note: It is required to provide a double backward slash '\\\' in any file paths (e.g. C:\\Proventeq\\MimeType.csv).

Example format for CSVInclude file.

A
HierarchyPath
E:\PMA Test Documents\Root\F2\F2-1
E:\PMA Test Documents\Root\F2\F2-3\F2-3-1
E:\PMA Test Documents\Root\F2\F2-4
E:\PMA Test Documents\Root\F2\F2-2
E:\PMA Test Documents\Root\F2\F2-3\F2-5

Example Limiting File Share discovery using CSVInclude using DateBefore

```
[{"FilterType":"DateBefore","ObjectType":"File","Filter":"7/5/2021"}]
```

For date filters, the date specified must be in the correct format as per the regional settings. This filter applies to the created date of the file.

Note: The date filter is not supported in delta discovery or processing.

Limiting Discovery using File Extensions - Using ExtensionInclude or ExtensionExclude

If the filter is an ExtensionInclude or ExtensionExclude list, a CSV file of relevant file extensions needs to be created. This is a simple list with each extension on a new line with the header "Type" e.g.

```
Type
.pdf
.txt
```

Extensions must begin with “.”

Using multi file properties to control Discovery

Several filter criteria can be used together if required. The criteria act as an ‘AND’ so for items to be discovered they must meet all criteria.

- [{"FilterType":"ExtensionInclude","ObjectType":"File","Filter": "C:\\\\Proventeq\\MimeType.csv"}, {"FilterType":"DateAfter","ObjectType":"File","Filter": "7/5/2021"}]

13.2.3. Discovery Filter for Documentum

Use the below discovery filter options to filter out cabinets, documents or folders while performing discovery. There are three types of discovery filter options supported:

- REST Service based Filter
- DQL Query based Filter
- CSV based Filter

Note Documentum DB connect type only supports CSV based filter. Documentum API connection type only supports Rest Service and DQL Query based filters.

REST Service Filter

REST service filter can be used to discover the folders or documents by iterating through give cabinets and folders hierarchy structure. So, it will discover the filtered documents or folders along with cabinet or folder structure.

Filter Format: [{"FilterType":"REST", "ObjectType":<ObjectType>, "Filter": "<Filter Criteria>"}]

Object Types:

The following Object Types are supported (Use numeric values):

- RootFolder = 2
- SubFolder=3
- Item = 4

Filter:

The following functions are supported in the filter

- contains
- starts-with
- between

Rest Filter Examples

Filter Criteria template for RootFolder with Contains function:

```
[{"FilterType":"REST","ObjectType":2,"Filter":"contains(object_name, 'Di') or  
contains(object_name, 'A')"}]
```

By using this filter expression, the request only returns objects whose object_name contains A.

Filter Criteria template for Items with starts-with function:

The starts-with function checks the starting string of a property.

```
[{"FilterType":"REST","ObjectType":4,"Filter":"starts-with(object_name, 'D')"}]
```

By using this filter expression, the request only returns **Items** whose object_name starts with D.

Filter Criteria template for Items with between function:

The between function returns items between a specified range. Check the format of the date provided in the filter.

```
[{"FilterType":"REST","ObjectType":4,"Filter":"between(r_modify_date, date('<date1>'),  
date('<date2>'))"}]
```

Eg:

```
[{"FilterType":"REST","ObjectType":4,"Filter":"between(r_modify_date, date('2014-03-02'),  
date('2017-09-10'))"}]
```

By using this filter expression, the request only returns objects whose r_modify_date is between 2014-03-02 and 2017-09-10.

DQL Query Filter

The DQL filter can only be used if connecting to Documentum API.

The DQL filter can be used to filter the documents across repository or in a particular cabinet/folder in a flat structure i.e. without iterating through cabinets/folders structure. So, discovery result will discover only filtered documents (similar to Documentum Search) without any cabinet or folder and its hierarchy/structure. DQL filter is not supported at virtual source containers like public or private cabinets level.

Filter Format: [{"FilterType":"DQL","ObjectType":"<ObjectType>","Filter":"<Condition1> **AND** (<Condition2> **OR** <Condition3>")}]

Here Filter Type will be as DQL, Object Type is the content or object type in the Documentum and Filter will be suitable DQL filter to discover specific set of documents.

Filter Criteria template for Items within specific Public/User Cabinet:

This filter will bring all the files under respective public/user cabinet id.

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"i_cabinet_id = '<Cabinet_ID>'"}]
```

Filter Criteria template for specific document and its versions:

This filter will bring given document id with all the versions.

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"i_chronicle_id = '<Chronicle_ID>'"}]
```

Filter Criteria template for Items between dates:

This filter will bring all the files creation date and modified date in between Date1 and Date2.

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"<Creation Date> > date('<date1>')  
and <Creation Date> < date('<date2>')"}]
```

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"<Modified Date> > date('<date1>')  
and <Modified Date> < date('<date2>')"}]
```

Filter Criteria template for specific document name:

This filter will bring the files with specific File Name.

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"object_name = '<File Name>'"}]
```

Filter Criteria template for Items containing repeatable attribute values:

This filter will bring the files with repeating attributes like tags having <Tag1> and <Tag2> values.

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"any <Repeating_Attribute> IN  
( '<Tag1>', '<Tag2>' )"}]
```

Eg:

```
[{"FilterType":"DQL","ObjectType":"dm_document","Filter":"any keywords IN  
( 'KeywordA', 'KeywordB' )"}]
```

Filter Criteria template for Items containing given name:

This filter will bring the files and its versions where <attribute> starts with <FileName>, ends with <FileName> and contains <FileName> respective to the Percentage(%) symbol specified.

A. This will bring <FileName> starts with given name.

```
["FilterType":"DQL","ObjectType":"dm_document","Filter":"<attribute> like '<FileName>%' "}]
```

B. This will bring <FileName> ends with give name.

```
["FilterType":"DQL","ObjectType":"dm_document","Filter":"<attribute> like '%<FileName>'"]
```

C. This will bring <FileName> containing given name.

```
["FilterType":"DQL","ObjectType":"dm_document","Filter":"<attribute> like '%<FileName>%'"]
```

CSV based Filter

A CSV based filter can be user to restrict the discovery based upon Documentum Cabinet ID for DocumentumDB connections. It will return all folders and items contained within the specified cabinets.

Filter Format:["FilterType":"**CSV**","ObjectType":"dm_cabinet","Filter":"<FilterCriteria>"]

FilterCriteria: One or more cabinet ids(i_cabinet_id) separated by comma.

Example: Filter Criteria template for single cabinet:

```
["FilterType":"CSV","ObjectType":"dm_cabinet","Filter":"0c0007c580009548,0c0003f270008498"]
```

Flatten discovery using CSV based Filter

Flatten discovery using **CSVFile** based filter is used for discovering documents underneath the provided r_object_id of the folder and its parent id (optional) in the CSV file

Filter Format: ["FilterType":"**CSV**","ObjectType":"<ObjectType>","FlatDiscovery":true or false,"Filter":"<Path of the file>"]

Filter: Filter contains the path of the file containing r_object_id of the folder and its parent id (optional) separated by comma.

Examples:

- **Filter Criteria template:**

```
["FilterType":"CSVFile","ObjectType":4,"FlatDiscovery":true,"Filter":"C:\\Documents\\Flat_discovery_build\\flat_discovery -modified.csv"]
```

	A	B
1	0b0d08d7800085e4	0b0d08d7800085e3
2	0b0d08d7800085e8	0b0d08d7800085e7
3		

The r_object_id should be provided in column A and its parent folder id in column B. Note that the \ must appear twice in folder paths.

13.2.4. Discovery Filter for OpenText

Filters can be applied for OpenText systems using Oracle or Microsoft SQL databases. Filtering can be applied to folders and documents.

These are list of tables and fields that can be used within filters.

Table Alias	Field
A for DTreeCore	DATAID, NAME, USERID, CreatedBy, ModifiedBy, CreateDate, Createdate, Modifydate, SubType, VersionNum
V for DVersData	VersionID, DocID, Version, VersionName, Owner, VerCDate, VerMDate, FILENAME, FileType, MimeType
K for KUAF	CreatedBy
K2 for KUAF	ModifiedBy
VK for KUAF	Owner

Below are the Sub Types available in OpenText for different entities which can be used in filters:

- 0 - Folder
- 144 - Documents
- 749 - Email
- 751 - Email Folder
- 136 - Compound Document
- 298 - Collection

Examples:

Filter based on Name from DTREECORE Table

To discover files where the A.Name property begins with specified value.

Product	Example Query
SQL	(A.Name like '<Name>%' AND A.SubType in (144)) OR (A.SubType in (0,751,298,136))
Oracle	(A.Name like '<Name>%' AND A.SubType in (144)) OR (A.SubType in (0,751,298,136))

Or even

(A.Name like '<Name>%' AND A.SubType in (0,144,751,298,136))

Just like standard SQL query syntax, use %. For example, <Name>% to find records that end with specified value or %<Name>% to find records that contain specified value.

Filter criteria based on CreateDate field from DTREECORE Table:

To discover files with Created Date greater than or equal to specified date. Note: Date should be in ISO format.

Product	Example Query
SQL	A.CreateDate >'2021-01-01' AND (A.SubType = 144 OR (A.SubType in (0,751,298,136)))

Oracle	A.SubType In (0, 144) AND A. CreateDate > TO_DATE('2021-01-01', 'yyyy-mm-dd') OR (A.SubType in (0,751,298,136))
--------	---

Filter criteria based on VerMDate field from DVersData Table:

To discover versions of documents with a modified date greater than specified date.

Product	Example Query
SQL	(V.VerMDate>'2021-05-06' AND A.SubType in (144)) OR (A.SubType in (0))

Discovery Filter for FileNet P8

The filter capabilities depend upon whether the FileNet P8 connection is configured to use API or Database.

API Filter

Filter Format:

```
[{"ObjectType":"2","Filter":"<Filter Criteria>"}]
```

The Object type determines the type of objects that can be found in the filter. The value of “2” represents “Files”, as this is the only type supported.

Examples:

- **Filter criteria based on Document Title:**

```
[{"ObjectType":"2","Filter":"(d.DocumentTitle like '<DocumentTitle>%')"}]
```

- **Filter criteria based on File Creator:**

```
[{"ObjectType":"2","Filter":"(d.Creator like '<FileCreatorName>%')"}]
```

Just like standard SQL query syntax, use %. For example, <FileCreatorName>% to find records that end with specified value or %<FileCreatorName>% to find records that contain specified value.

- **Filter criteria based on Date Modified**

To discover the files based on Date created that is greater than or equal to the given <Date>. The date should be in ISO format.

```
[{"ObjectType":"2","Filter":"d.DateLastModified >= <DateModified>"}]
```

- **Filter criteria based on Class or Content Type:**

To discover files based on Class or Content Type.

```
[{"ObjectType":"2","Filter":"(IsOfClass(d, <ContentType>))"}]
```

Example a list of items with a Content Type/Class of “Communication” or “Policy”

E.g. [{"ObjectType": "2", "Filter": "(IsOfClass(d, Communication) OR IsOfClass(d, Policy))"}]

- **Filter criteria based on Metadata:**

To discover the files based on metadata properties.

[{"ObjectType": "2", "Filter": "(<PropertyName>='PropertyValue')"}]

E.g. [{"ObjectType": "2", "Filter": "(BankName='Indian Bank' OR BankName='Overseas Bank')"}]

Database Filter

Note: The Database filter requires table alias and database column/fields name. e.g. to apply filter on DocumentTitle column name in database must use table alias “d” and column name “u1708_documenttitle”.

Filter Format: [{"ObjectType": <ObjectType>, "Filter": "<Filter Criteria>"}]

Table Alias	Fields
D for DocVersion	object_id, mime_type , version_series_id, major_version_number , minor_version_number, create_date, creator, modify_date, modify_user, compound_document_state , 1708_documenttitle , Modify_user and custom property fields
CR for Current DocVersion	object_id, mime_type , version_series_id, major_version_number , minor_version_number, create_date, creator, modify_date, modify_user, compound_document_state , 1708_documenttitle , Modify_user and custom property fields
CD for ClassDefinition	symbolic_name

D queries against all versions, **CR** queries against latest version of documents.

Object Type:

The following Object Type is supported (Use numeric value):

- File = 2

Examples:

Filter criteria based on Document Title:

To discover the files that starts with given <DocumentTitle>.

```
[{"ObjectType":"2","Filter":"(D.u1708_documenttitle like '<DocumentTitle>%' )","Uri":"","IsRecursive":true}]
```

Just like standard SQL query syntax, use %. For example, <DocumentTitle>% to find records that end with specified value or %<DocumentTitle>% to find records that contain specified value.

- **Filter criteria based on File Modifier:**

To discover the files based on Modifier that starts with given <FilemodifierName>.

```
[{"ObjectType":"2","Filter":"(D.modify_user like '%<FilemodifierName>')","Uri":"","IsRecursive":true}]
```

- **Filter criteria based on Date Last Modified:**

To discover documents were the latest version has a modified date greater than specified date.

```
[{"ObjectType":"2","Filter":"CR.modify_date><ModifiedDate>","Uri":"","IsRecursive":true}]
```

The date can be in the format depending on FileNet datetime format.

E.g. [{"ObjectType":"2","Filter":"CR.modify_date>'2020-06-01'","Uri":"","IsRecursive":true}]

- **Filter criteria based on Class or Content Type:**

To discover the files based on Class or Content Type.

```
[{"ObjectType":"2","Filter":"(CD.symbolic_name='<ContentType>')","Uri":"","IsRecursive":true}]
```

E.g. [{"ObjectType":"2","Filter":"(CD.symbolic_name='Communication' OR CD.symbolic_name='Policy')","Uri":"","IsRecursive":true}]

- **Filter criteria based on Metadata:**

To discover the files based on metadata properties.

```
[{"ObjectType":"2","Filter":"(D.<PropertyName> = '<PropertyValue>')","Uri":"","IsRecursive":true}]
```

E.g. [{"ObjectType":"2","Filter":"(D.u06a8_bankname='Indian Bank' OR D.u06a8_bankname='Overseas Bank')","Uri":"","IsRecursive":true}]

13.2.5. Discovery Filter for iManage

Filters can be used to limit discovery to workspaces, container(folders) and documents by allowing queries against RootContainer, Container and Item tables respectively.

Filter Type	Description	Filter Query Syntax
-------------	-------------	---------------------

Root Container (Workspace)	To filter particular workspace	{"RootContainer" : "Root.PRJ_NAME = '<Workspace Name>'"}
	To filter multiple workspaces	{"RootContainer" : "Root.PRJ_NAME in ('<Workspace Name>', '<Workspace Name2>')"}
Container	To filter specific folder.	{"RootContainer" : "Root.PRJ_NAME = '<Workspace Name>', "Container" : "(Container.ItemName = '<Folder Name>' AND Container.EntityType = 'Folder')"}
Item	To filter specific item inside the specific folder.	{"RootContainer" : "Root.PRJ_NAME = '<Workspace Name>', "Container" : "(Container.ItemName = '<Folder Name>' AND Container.EntityType = 'Folder')", "Item" : "Item.DoNum = '<Document Number>'"}
	To filter items with date created filter	{"Item" : "Item.EntryWhen > '<Date>'"}
	To filter items with date modified filter	{"Item" : "Item.EditWhen > '<Date>'"}

The <Workspace Name>, <Folder Name>, <Document Number> and <Date> should be replaced with the respective values as mentioned in above query. Standard SQL operators can be used in these filters.

13.2.6. Discovery Filter for M-files

Filters can be used to limit discovery to specific classes

Filter Criteria template:

Filter Syntax:

```
{
  "FilterType": "ClassList",
  "Filter": "C:\\mfilesclasslist\\discoveryfilter.csv"
}
```

Example File: discoveryfilter.csv .Note: ClassName is a mandatory column heading.

ClassName

Contracts

Filter M-Files Document ID

```
[{"FilterType":"FileList","Filter":"C:\\MigrationData\\discoveryfilter.csv"}]
```

Example File: discoveryfilter.csv. Note: FileId is a mandatory column heading.

FileId,Type

1,

2,

44444,

13.2.7. Discovery Filter for Alfresco

Filters can be used to limit discovery to specific sites.

Filter Criteria template for sites:

Filter Syntax:

```
[{"ObjectType":"Site","Filter":"<SiteName>"}]
```

Example - Discovery all folders and documents within "Insurance" site.

```
[{"ObjectType":"Site","Filter":"Insurance"}]
```

Note: To filter multiple sites a comma separated list can be provided. E.g.

```
[{"ObjectType":"Site","Filter":"Insurance,HR"}]
```

13.2.8. Discovery Filter for Oracle UCM

Filter is only support for items not contained within folders, i.e. no parent folder. Filtering on Contribution Folders and Framework Folders is not supported.

Filter Syntax:

```
dDocName='<DocumentName>'
```

```
dDocType='<DocumentType>'
```

Examples

```
dDocName = 'PROV_PROV_090007C280000583'
```

```
dDocType = 'Document'
```

13.2.9. Discovery Filter for Hummingbird/EDocs

You can filter upon documents and folders based on a variety of criteria like Matter, SubMatter, DOCNUMBER, etc. Below are the table alias to use in Discovery Filter.

DP : Profile Table (DOCSADM.Profile)

DV : Versions Table (DOCSADM.Versions)

The filter needs to contain the SQL clause filter string like below:

Dynamic Filter	Description
DP.E_DIVPROJ ='<ID>'	This filter will get folders and documents of respective ID provided in Discovery filter.
DP.CREATION_DATE BETWEEN '<Date1>' AND '<Date2>'	This filter will get the documents created between the Date1 and Date2.
DP.CREATION_DATE > '<Date>'	This filter will get the documents created from the given date.
DV.DOCNUMBER in ('DOCNUM1', DOCNUM2)	This filter will get the all the folders and the documents which are provided in Discovery Filter.

13.2.10. Discovery Filter for BOX

A filter can be applied to the Discovery. Using a filter can speed up the discovery process, as well as reduce the size of the databases created by discovery and ensures that the database doesn't contain any items which do not have to be migrated. Anything not discovered will not be processed for migration.

Discovery Filter Syntax:

It is required to provide a double backward slash '\\' in any file paths (e.g. C:\\Proventeq\\).csv).

Inclusion Filter - Include only specified users/folders:

```
[{"ObjectType": "CSV", "Filter": "path\\to\\infil.csv"}]
```

The inclusion filter requires a URL of a folder to include in the discovery (FolderURL), and the username or login email of the owner (UserName, this is required due to how Box handles permissions and service accounts).

A user's content root (the "All Files" folder) can be included by providing the user content root URL (e.g. <https://app.box.com/folder/0>) with the user's info, as in the example below.

FolderURL,UserName

<https://app.box.com/folder/158718117193>,Corp Admin

<https://app.box.com/folder/158718322420>,dev@acmecorp.com

<https://app.box.com/folder/0>,other_user@acmecorp.com

Exclusion Filter - Exclude only specified users/folders:

```
[{"ObjectType":"CSV","FilterType":"CSVExclude","Filter":"path\\to\\exfil.csv"}]
```

The exclusion filter only needs the URLs of the folders to exclude. No user information needs to be provided. The exclusion filter does not currently support excluding user root content folders.

FolderURL

<https://app.box.com/folder/159258028738>

<https://app.box.com/folder/159259572184>

14. APPENDIX 2 - PROGRAMMING

Target metadata fields can be populated using the output of a programming function. The programming function can be a single built-in function, or from the output of a customer written PowerShell script.

Target Field	Parameter Type	Value
Author	Function	TOUPPER(SrcAuthor)

In the example above the Author field in the target is populated using a function which takes the value of the source metadata field SrcAuthor field and applies the TOUPPER function to it to set all characters to uppercase.

14.1. Built-in Functions

The full list of functions available to populate Target Metadata fields.

14.1.1. String Functions

Function Name	Parameters	Description
ConcatWithSeparator	Separator, stringOne, stringTwo	This function allows you to combine two different strings with your separator.
Concat	stringOne, stringTwo	This function will join two strings.
StringContains	stringToCheck, orgString	This function will check one string contains other supplied string or not. It will return value as true or false.
ReplaceString	orgString, wantToReplace, replaceString	This function will replace sting.
SubstringByStartPosition	orgString, startPosition	This function will return sting from your supplied position.
SubstringByPostionAndLength	orgString, startPosition, length	This function will return sting from your supplied position and length.
ToUpper	Name	Changing text case to upper
ToLower	Name	Changing text case to lower
Compare	stringOne, stringTwo	Comparing two string values

14.1.2. Math Functions

Function Name	Parameters	Description
SUM	stringOne, stringTwo	This function will return sum of given two numbers.
Round	Value, RoundUpto	Returning a decimal value to the nearest integral value
Absolute	Value	Returning the absolute value of a Decimal number
Power	Value, PowerUpto	Returning a specified number raised to the specified power

14.1.3. Date Functions

Function Name	Parameters	Description
Now()		This function will return current datetime value.
Get-Day	Date	This function will return day value from given date.
Get-Month	Date	This function will return month value from given date.
Get-Year	Date	This function will return year value from given date.
Get-Time	Date	This function will return time value from given date.
Get-DateFormat[yyyy-MM-dd]	Date	This function will return given date in yyyy-MM-dd format.
Get-DateFormat[dd-MM-yyyy]	Date	This function will return given date in dd-MM-yyyy format.

14.1.4. Misc Functions

Function Name	Parameters	Description
GetMappedUser	srcMetaValue	This function will give target mapped for given source user based on user mapping.
Substitute_Invalid_Characters	inputString	This function will substitute invalid characters in given input string that are not supported by target system.
GetTargetTaxonomy	sourceTaxonomy	This function will give target taxonomy value for given source taxonomy value.
Get-Newname	Name, Ext	This function will return a new name after combining name and extension of file.
Get-PathSegment	Url, SegmentNumber	This function will return path segment from given Url.

GetTargetContentItemIdBySourceUri	srcMetaValue	This function will return target content item id based on source item Uri.
-----------------------------------	--------------	--

14.1.5. OCR Functions

Function Name	Parameters	Description
Get-OCRText	srcMetaValue	This function will read text field from Image file by rendering text pattern.
Get-OCRDateField	srcMetaValue	This function read date field from Image by rendering through date pattern.
Get-OCRWordField	srcMetaValue	This function will return specific word from string by rendering image
Get-OCRSpaceDelimitedField	srcMetaValue	This function will return field which is space separated with field value by rendering image
Get-OCRTerminatedField	srcMetaValue	
Get-OCRNumberField	srcMetaValue	
Get-OCRFourColumnNumber	srcMetaValue	This function will return four column values separated '/'.
Get-OCRMonthYear	srcMetaValue	This function will return Month year value from Date field.
Get-OCRYear	srcMetaValue	This function will return Year value from Date field.

14.2. Creating Lookup tables for Custom Functions

Often target metadata may need to be supplemented with additional data from a CSV file. For example, a table of information for each employee where a lookup using the EmployeeID from the source item is then used to return the user's department, line manager, grade level etc. from a .CSV file.

In such cases, a Target metadata property can be mapped to a PowerShell script which can lookup in a CSV file for relevant information. If the lookup file(.CSV) were to occur every time an item is processed, this approach would severely impact migration performance, especially when using large lookup tables.

To resolve such issues, PMA has the ability for a .CSV file to be loaded only once per migration thread instead of for each item.

Note: This feature is only supported on non SaaS installations of PCS.

1. Design CSV file

The CSV file must contain a unique Item ID column (effectively a column that acts as a key), and columns for all the Metadata associated with the item.

EmployeeID,	FirstName,	Surname,	DOB
0001,	Jane,	Potter,	16/2/1962
0002,	Sarah,	Mahoney,	28/4/1995
0003,	Rosemary,	Sharkey,	3/3/1975

Example EmployeeDatabase.CSV

EmployeeID is the key and there are three columns FirstName, Surname and DOB

2. Creating new PowerShell module

A new PowerShell module file (.PSM1 file) needs to be created which will be executed once by each thread basis to load the data.

e.g. Datatable_Load.psm1

3. Use PowerShell to import CSV.

Edit the new PowerShell script Datatable_Load.psm1 to create a script to load the .CSV file.

Syntax to create a global variable and import the CSV

```
$global:<VariableToHoldCSV> = Import-CSV -path '<My csv path>'
```

e.g.

```
$global:Employee_Metadata = Import-CSV -path 'c:\datamigration\EmployeeDatabase.CSV'
```

When the script is executed the Employee_Metadata global variable will contain the contents of the CSV file.

4. Add reference to new PowerShell module

PMA needs to be configured to load this new PowerShell module.

Open Notepad in Administrator mode and open the main Proventeq PowerShell Module

Proventeq.MigrationAccelerator.PowerShell.Module.psd1 (typically located in C:\Program Files\Proventeq\Proventeq Migration Accelerator\PowerShell)

Update the **NestedModule** property

of **Proventeq.MigrationAccelerator.PowerShell.Module.psd1** file to include this new module (e.g., Datatable_Load.psm1). Typically

```
NestedModules =
@("Proventeq.MigrationAccelerator.SharePointModule.psm1", "Proventeq.MigrationAc
celerator.PowerShellModule.psm1", "c:\datamigration\Datatable_Load.psm1")
```

After this change, starting PMA will execute the PowerShell script.

When the threads start, they will execute the module `Datatable_Load.psm1` which will execute the above PowerShell to load the CSV into a global variable `DOB_Metadata` for the Custom Function to use.

14.2.1. Using the Imported Data

The PowerShell script executed by the Custom Function can now use the data as follows.

```
$EmployeeDatabase = $global:Employee_Metadata | ?{$_EmployeeID -eq $EmployeeID}
Return $EmployeeDatabase.DOB
```

In the example above, a variable `$EmployeeID` is used to find a matching entry by looking up the `.EmployeeID` field in the `Employee_Metadata` global variable. The script then returns the `.DOB` field for that record.

Testing PowerShell Functions

It is recommended to test any changes made to the PowerShell module prior to launching PMA. The following steps can be executed to validate the changes.

Open PowerShell console and import the Proventeq PowerShell module

```
"C:\Program Files\Proventeq\Proventeq Content Suite
\PowerShell\Proventeq.MigrationAccelerator.Module.psd1" -Force
```

Add/Edit Function

Functions can be used to populate fields. [Learn more](#)

Name*		Description	
DOBLookup		Lookup DOB for Employee	
Group*			
Custom Scripts			
Parameters for this Function		Specify test values for parameters below to confirm function behavior is correct	
Name	Type	Name	Test value
EmployeeID	String	EmployeeID	00002
Script		Function Testing output	
<pre>1 \$EmployeeDatabase = \$global:Employee_Metadata ?{\$_EmployeeID -eq \$EmployeeID} 2 Return \$EmployeeDatabase.DOB</pre>			

FIGURE 106 - ANALYTICS – EXAMPLE FUNCTION USING IMPORTED DATA

In the example above you can see the EmployeeID variable defined as a string and below that the Script to execute. On the right is Test Data window where the value 0002 is passed to the function and it correctly returns in the Text View the DOB of 28/4/1995 based upon the values in the CSV EmployeeDatabase.CSV which is held in Employee_Metadata global variable.

Controlling how parameters are passed to the Custom Function

In the properties of the function, specify how the parameter value will be passed to the customer function. In the example below, the EmployeeID value comes from the Name metadata field.

Specify details of parameters to be passed to selected function. For each parameter specify if a constant value or a source metadata field should be used.

Parameter Name	Parameter Type	Source
EmployeeID	Metadata	Name

FIGURE 107 - CONFIGURE HOW DATA IS PASSED IN AS PARAMETER TO FUNCTION

14.2.2. BOX API Consumption

Below are details of how PMA consumes BOX API resources. This can give an indication of how much BOX API licence consumption may occur during a migration. It's essential to discuss BOX API limits with your BOX Account Manager.

- Discovery**
 - 1 API call per folder to retrieve a list of subfolders and files.
 - 1 API call per file to discover the sharing permissions (if security discovery is enabled and the file has been shared with other users).
 - 1 API call per file to discover the version history (if version discovery is enabled and the file has previous versions).
 - A small number of calls per discovery run for setup (get user ID mappings, discover the initial folder / discovery filter entries, etc).
- Migration**
 - 1 API call per file version to download the file to the migration server.
- Misc**
 - A small number of calls when adding Box as a source connection to populate the folder selector.

Note: Some of these API methods are paginated at 1000 items, so it takes 1 call per 1000 entries. For example, if a folder contains 2500 files, it would take 3 API calls to get the full list of items.

